

## DESIGNER'S NOTES FOR DETAILS AND SCHEDULES

1. REFER TO DESIGNER'S NOTES ON THE DETAILS. REMOVE DESIGNER'S NOTES PRIOR TO ISSUING.
2. GROUP COMMON DETAILS, SUCH AS PIPING, AS MUCH AS POSSIBLE.
3. MANUAL AIR VENTS ARE REQUIRED ON CHILLED AND HEATING HOT WATER SYSTEMS AND AT LOCAL HIGH POINTS. LOCAL HIGH POINT IS A SECTION OF PIPE AT A HIGHER ELEVATION THAN THE SECTION OF PIPE IMMEDIATELY DOWNSTREAM AND IMMEDIATELY UPSTREAM.
4. FOR EQUIPMENT SCHEDULES:
  - A. PROVIDE SCHEDULES FOR EXISTING FANS OR OTHER EQUIPMENT THAT MUST BE MODIFIED OR REBALANCED. SHOW EXISTING AND FUTURE CAPACITIES AND MOTOR SIZES.
  - B. DO NOT USE DITTO MARKS FOR REPETITIVE ENTRIES.
  - C. USE IN SCHEDULES WHERE THE COLUMN HEADING IS NOT APPLICABLE TO INDICATE THAT THE LACK OF AN ENTRY WAS NOT AN OMISSION.
  - D. GROUP SCHEDULES AS MUCH AS POSSIBLE. SEE HVAC DESIGN MANUAL FOR SEQUENCE OF SCHEDULES.
5. ALL DUCTWORK, WITHOUT EXCEPTION, AND ALL PIPING 150mm [6"] AND LARGER SHALL BE SHOWN IN DOUBLE LINE.

## ABBREVIATION AND SYMBOL NOTES

1. THE COMPOSITE LIST OF ABBREVIATIONS IS COORDINATED WITH THE UNITED STATES NATIONAL CAD STANDARD VERSION 4.0, LEGACY VA LIST OF ABBREVIATIONS, AND ASHRAE. THIS LIST SHALL BE USED FOR ALL VA PROJECTS AND EDITED, AS REQUIRED, TO BE PROJECT SPECIFIC. THE DESIGNER MAY SELECT AND USE ADDITIONAL ABBREVIATIONS, IF REQUIRED, FROM ANY KNOWN SOURCES.
2. THE LIST OF SYMBOLS IS MOSTLY BASED ON THE VA MASTER LIST OF STANDARD SYMBOLS AND HAS BEEN UPDATED IN CONSULTATION WITH OTHER SOURCES, SUCH AS, NATIONAL CAD STANDARD VERSION 4, AND ISA (THE INSTRUMENTATION, SYSTEMS, AND AUTOMATION SOCIETY). THIS LIST SHALL BE USED FOR ALL VA PROJECTS AND EDITED, AS REQUIRED, TO BE PROJECT SPECIFIC. THE DESIGNER CAN SELECT AND USE ADDITIONAL SYMBOLS, IF REQUIRED, FROM ANY KNOWN SOURCE



Department of  
Veterans Affairs

DETAIL TITLE: DESIGNER NOTES FOR DETAILS AND SCHEDULES

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-01.DWG

GENERAL NOTES

1. ALL PIPING AND DUCTS IN FINISHED ROOMS OR SPACES SHALL BE CONCEALED IN A FURRED CHASE OR ABOVE HARD SUSPENDED CEILING, OR ACOUSTICAL CEILING.
2. THE FIRST FIGURE OF DUCT SIZE INDICATES DIMENSION OF FACE SHOWN OR INDICATED. DUCT SIZES ARE NET INSIDE DIMENSIONS.
3. ACCESS PANELS IN HARD SUSPENDED CEILINGS ARE REQUIRED FOR ALL VALVES, TRAPS, DAMPERS, CLEANOUTS, CONTROLS, ETC. ACCESS PANELS SHALL BE FURNISHED AND INSTALLED UNDER THE ARCHITECTURAL SPECIFICATIONS. COORDINATE LOCATION WITH MECHANICAL INSTALLATION AND DEMONSTRATE ACCESS TO EQUIPMENT SERVED.
4. TOTAL STATIC PRESSURE NOTED IN THE SCHEDULES INCLUDES DUCT SYSTEM, TERMINAL UNITS, FILTERS, COILS, ETC. LOSS FOR FILTERS SHALL BE FOR FILTERS AT 50% LOADING.
5. FOR TYPICAL STEAM AND WATER PIPING CONNECTIONS TO EQUIPMENT, SEE STANDARD EQUIPMENT DETAILS.
6. DIFFUSER, REGISTER AND GRILLE SIZES SHOWN ON FLOOR PLANS ARE NECK SIZES.
7. WATER PIPE CONNECTIONS TO AIR HEATING AND COOLING COILS SHALL BE MADE TO PROVIDE COUNTER FLOW BETWEEN WATER AND AIR.
8. WALL TYPE EXHAUST REGISTERS NOTED AS "BR" ON DRAWINGS ARE TO BE INSTALLED WITH BOTTOM ELEVATION OF REGISTER AT 175mm [7"] ABOVE FINISHED FLOOR.
9. REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATIONS OF CEILING DIFFUSERS, REGISTERS, AND GRILLES.
10. STEAM HEADER SET PRESSURE:     \_\_\_ kPa [PSIG] NORMAL  
  \_\_\_ kPa [PSIG] LOW DEMAND PERIODS
11. ALTITUDE-BOILER ROOM FLOOR:     \_\_\_ M [FT.] ABOVE SEA LEVEL
12. SEISMIC PROVISIONS // REQUIRED – SEE SPECS // NOT REQUIRED //  
    ALL PRESSURES LISTED ARE GAGE PRESSURE UNLESS OTHERWISE NOTED



Department of  
Veterans Affairs

DETAIL TITLE: GENERAL NOTES

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-02.DWG

## ABBREVIATIONS

A/E	ARCHITECT / ENGINEER	C	CENTIGRADE (CELSIUS)
AAHX	AIR TO AIR HEAT EXCHANGER	CAV	CONSTANT AIR VOLUME
AAV	AUTOMATIC AIR VENT	CC	COOLING COIL
AB	AIR BLENDER	CCD	COOLING COIL CONDENSATE DRAIN
ACC	AIR COOLED CONDENSER	CD	CEILING DIFFUSER
ACCH	AIR COOLED CHILLER	CD-1	CONSTRUCTION DOCUMENTS (SUBMISSION1)
ACCU	AIR COOLED CONDENSING UNIT	CD-2	CONSTRUCTION DOCUMENTS (SUBMISSION2)
ACD	AUTOMATIC CONTROL DAMPER, MODULATING	CENT	CENTRIFICAL
ACD-TP	AUTOMATIC CONTROL DAMPER, TWO POSITION	CFH	CUBIC FEET PER HOUR
ACU	AIR CONDITIONING UNIT	CFM	CUBIC FEET PER MINUTE
AD	ACCESS DOOR	CFT	CUBIC FEET
AF	AFTER FILTER	CFP	CHEMICAL FEED PUMP
AFCV	AIR FLOW CONTROL VALVE	CG	CEILING GRILLE
AFF	ABOVE FINISHED FLOOR	CH	CHILLER
AFMS	AIR FLOW MEASURING STATION	CHP	CHILLED WATER PUMP
AFW	AIR FOIL WHEEL (FAN)	CHW	CHILLER WATER
AHU	AIR-HANDLING UNIT	CHR	CHILLED WATER RETURN
AMP	AMPERE	CHS	CHILLED WATER SUPPLY
AP	ACCESS PANEL	CI	CAST IRON
APD	AIR PRESSURE DROP	CM	CARBON MONOXIDE
AQST	AQUASTAT	CM	CUBIC METER
ARI	AIR CONDITIONING AND REFRIGERATION INSTITUTE	CM/S	CUBIC METER PER SECOND
AS	AIR SEPARATOR	CO	CLEAN OUT
ASHRAE	AMERICAN SOCIETY OF HEATING REFRIGERATION AIR CONDITIONING ENGINEERS	CO2	CARBON DIOXIDE
ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS	COMP	COMPRESSOR UNIT
AW	AIR WASHER	COP	COEFFICIENT OF PERFORMANCE
AXF	AXIAL FLOW	CP	CONDENSATE PUMP
		CR	CEILING REGISTER
		CS	CONDENSATE STORAGE TANK
		CSG	CLEAN STEAM GENERATOR
		CT	COOLING TOWER
		CU	CONDENSING UNIT
		CUH	CABINET UNIT HEATER
		CV	CONSTANT VOLUME
B	BOILER	CW	COLD WATER (POTABLE)
BD	BUTTERFLY DAMPER	CWCC	CHILLED WATER COOLING COIL
BDD	BACKDRAFT DAMPER	CWP	CONDENSER WATER PUMP
BDR	BASE BOARD RADIATOR	CWR	CONDENSER WATER RETURN (TO COOLING TOWER)
BFP	BACKFLOW PREVENTER		
BFT	BOILER PLANT FIRE TUBE	CWS	CONDENSER WATER SUPPLY (FROM COOLING TOWER)
BG	BOTTOM GRILLE		
BHP	BRAKE HORSEPOWER		
BHW	HOT WATER HEATING BOILER		
BHX	BOILER BLOWDOWN HEAT EXCHANGER		
BIW	BACKWARD INCLINED WHEEL (FAN)		
BMT	BONE MARROW TRANSPLANT		
BR	BOTTOM REGISTER	D	DAMPER - AUTOMATIC
BSC	BIOLOGICAL SAFETY CABINETS	Db	DRY-BULB TEMPERATURE
BT	BLOWOFF TANK	DB	DECIBELS
BTC	BLOWOFF TANK CONTROL VALVE	DCW	DOMESTIC COLD WATER
BTU	BRITISH THERMAL UNIT	DD-1	DESIGN DEVELOPMENT (SUBMISSION 1)
BTUH	BRITISH THERMAL UNIT PER HOUR	DD-2	DESIGN DEVELOPMENT (SUBMISSION 2)
BWT	BOILER PLANT WATER TUBE	DDC	DIRECT DIGITAL CONTROLS
		DEG	DEGREE
		DF	DIFFUSER
		DHW	DOMESTIC HOT WATER
		DHWR	DOMESTIC HOT WATER RETURN
		DIA	DIAMETER
		DIW	DEIONIZED WATER
		DP	DEW POINT TEMPERATURE
		DP	DIFFUSER PLATE
		DPA	DIFFERENTIAL PRESSURE ASSEMBLY
		DPS	DIFFERENTIAL PRESSURE SENSOR
		DX	DIRECT EXPANSION
		DXCC	DIRECT EXPANSION COOLING COIL



Department of  
Veterans Affairs

DETAIL TITLE: ABBREVIATIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-03.DWG

## ABBREVIATIONS

EA	EXHAUST AIR	GA	GAUGE
EAT	ENTERING AIR TEMPERATURE	GAL	GALLONS
EC	EVAPORATIVE COOLER	GH	GRAVITY HOOD
ECC	ENGINEERING CONTROL CENTER	GPD	GALLONS PER DAY
ECU	EVAPORATIVE CONDENSER UNIT	GPH	GALLONS PER HOUR
EDH	ELECTRIC DUCT HEATER	GPM	GALLONS PER MINUTE
EER	ENERGY EFFICIENCY RATIO	GPR	GAS PRESSURE REGULATOR
EF	EXHAUST FAN	GS	GALVANIZED STEEL
EG	EXHAUST GRILLE		
EGS	EMERGENCY GAS SHUTOFF		
EGT	ENTERING GLYCOL TEMPERATURE	H	HUMIDIFER
EH	EXHAUST HOOD	HAC	HOUSEKEEPING AID CLOSET
EJ	EXPANSION JOINT	HB	HOSE BIBB
EMD	END OF MAIN DRIP (STEAM)	HC	HEATING COIL
ENT	ENTERING	HD	HOOD
ER	EXHAUST REGISTER	HOA	HAND/OFF/AUTOMATIC
ERC	ELECTRIC REHEAT COIL	HP	HEAT PUMP
ERP	ELECTRIC RADIANT PANEL	HP	HORSEPOWER
ESP	EXTERNAL STATIC PRESSURE	HPDT	HIGH PRESSURE DRIP TRAP
ET	EXPANSION TANK	HPR	HIGH PRESSURE RETURN (STEAM CONDENSATE)
ETO	ETHYLENE OXIDE		
EUH	ELECTRIC UNIT HEATER	HPS	HIGH PRESSURE SUPPLY (STEAM)
EWC	EVAPORATIVE WATER COOLER	HRC	HEAT RECOVERY COIL
EWT	ENTERING WATER TEMPERATURE	HRD	HEAT RECOVERY DEVICE
EX	EXISTING	HRP	HYDRONIC RADIANT (CEILING) PANEL
		HRW	HEAT RECOVERY WHEEL
		HSTAT	HUMIDISTAT
F	FAHRENHEIT	HTM	HUMIDIFIER TERMINAL
F&T	FLOAT AND THERMOSTATIC	HUM	HUMIDIFIER UNIT MOUNTED
F/SDPR	COMBINATION FIRE SMOKE DAMPER	HVU	HEATING AND VENTILATING UNIT
FA	FREE AREA	HW	HOT WATER
FC	FLEXIBLE CONNECTION	HWC	HOT WATER COIL
FCU	FAN COIL UNIT (4 PIPE)	HWHC	HOT WATER HEATING COIL
FCUC	FAN COIL UNIT COOLING ONLY	HWP	HEATING HOT WATER PUMP
FCUH	FAN COIL UNIT HEATING ONLY	HWR	HEATING HOT WATER RETURN
FCW	FORWARD CURVED WHEEL (FAN)	HWS	HEATING HOT WATER SUPPLY
FD	FLOOR DRAIN	HWUH	HOT WATER UNIT HEATER
FD	FIRE DAMPER	HVD	HOISTWAY VENT DAMPER
FF	FINAL FILTER	HX	HEAT EXCHANGER
FHX	FLUE GAS/FEEDWATER HEAT EXCHANGER	HZ	HERTZ
FM	FLOW METER		
FOP	FUEL OIL PUMP		
FOT	FUEL OIL TANK		
FOHX	FUEL OIL HEAT EXCHANGER		
FPM	FEET PER MINUTE		
FPS	FEET PER SECOND		
FPTU	FAN POWERED TERMINAL UNIT		
FR	FLOOR REGISTER		
FRP	FIBER REINFORCED POLYESTER		
FS	FLOW SWITCH		
FSTAT	FREEZESTAT		
FT	FEET		
FT WC	FEET OF WATER COLUMN		
FT-LB	FOOT-POUND		
FTR	FIN TUBE RADIATION		
FV	FACE VELOCITY		



Department of  
Veterans Affairs

DETAIL TITLE: ABBREVIATIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-04.DWG

## ABBREVIATIONS

I/O	INPUT/OUTPUT	M	METER, SI UNIT
IAQ	INDOOR AIR QUALITY	M/S	METERS PER SECOND (OR METERS/SECOND)
IBT	INVERTED BUCKET TRAP	MA	MIXED AIR
ICF	IN-LINE CENTRIFUGAL FAN	MAT	MIXED AIR TEMPERATURE
ICU	INTENSIVE CARE UNIT	MAU	MAKE-UP AIR UNIT
ID	INSIDE DIAMETER	MAV	MANUAL AIR VENT
IFB	INTEGRAL FACE AND BYPASS	MAX	MAXIMUM
IN	INCHES	MB	MIXING BOX
IN HG	INCHES OF MERCURY	MBH	1,000 BTUH
IN WC	INCH WATER COLUMN	MCA	MINIMUM BRANCH CIRCUIT AMPACITY
IN WG	INCH WATER GAUGE	MER	MECHANICAL EQUIPMENT ROOM
IN-LB	INCH-POUND	MERV	MINIMUM EFFICIENCY REPORTING VALUE
IPLV	INTERGRATED PART LOAD VALUE	MH	MANHOLE
IRH	INTRARED HEATER	MHP	MOTOR HORSEPOWER
IS	INSECT SCREEN	MIN	MINIMUM
IU	INDUCTION UNIT	MM	MILLIMETER
IV	INLET VANES	MOV	MOTOR OPERATED VALVE
		MPR	MEDIUM PRESSURE RETURN (STEAM CONDENSATE)
J	INTENTIONALLY LEFT BLANK	MPS	MEDIUM PRESSURE STEAM
		MRI	MAGNETIC RESONANCE IMAGING
KG	KILOGRAM	MTD	MEAN TEMPERATURE DIFFERENCE
KG/HR	KILOGRAM PER HOUR	MVD	MANUAL VOLUME DAMPER
kPa	KILOPASCAL	MZ	MULTI-ZONE
KW	KILOWATT		
KWH	KILOWATT HOUR		
		NA	NOT APPLICABLE
L	LITER	NC	NOISE CRITERIA
L/h	LITERS PER HOUR (or LITERS/HOUR)	NC	NORMALLY CLOSED
L/m	LITERS PER MINUTE (or LITERS/MINUTE)	NG	NATURAL GAS
L/s	LITERS PER SECOND (or LITERS/SECOND)	NGFM	NATURAL GAS FLOWMETER
LAT	LEAVING AIR TEMPERATURE	Nm	NEWTON METER
LBS/HR	POUNDS PER HOUR	NO	NORMALLY OPEN
LF	LINEAR FOOT (FEET)	NOAA	NATIONAL OCEANIC & ATMOSPHERIC ADMINISTRATION
LGT	LEAVING GLYCOL TEMPERATURE	NOM	NOMINAL
LH	LATENT HEAT	NPLV	NON-STANDARD PART LOAD VALUE
LPG	LIQUEFIED PETROLEUM GAS	NPSH	NET POSITIVE SUCTION HEAD
LPR	LOW PRESSURE RETURN (STEAM CONDENSATE)	NPSHA	NET POSITIVE SUCTION HEAD AVAILABLE
LPRC	LOW PRESSURE STEAM RETURN (CLEAN)	NPSHR	NET POSITIVE SUCTION HEAD REQUIRED
LLHX	LIQUID TO LIQUID HEAT EXCHANGER	NTS	NOT TO SCALE
LPS	LOW PRESSURE STEAM		
LPSC	LOW PRESSURE STEAM (CLEAN)	OA	OUTSIDE AIR
LSD	LINEAR SLOT DIFFUSER	OAD	OUTDOOR AIR DAMPER
LTCP	LOCAL TEMPERATURE CONTROL PANEL	OAG	OUTSIDE AIR GRILLE
LVG	LEAVING	OAI	OUTSIDE AIR INTAKE
LVR	LOUVER	OD	OUTSIDE DIAMETER
LWT	LEAVING WATER TEMPERATURE	OFM	OIL FLOWMETER
		OR	OPERATING ROOM



Department of  
Veterans Affairs

DETAIL TITLE: ABBREVIATIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-05.DWG

## ABBREVIATIONS

P	PUMP	SA	SUPPLY AIR
Pa	PASCAL	SAD	SOUND ATTENUATING DEVICE
PC	PUMPED CONDENSATE	SAT	SUPPLY AIR TEMPERATURE
PCF	POUNDS PER CUBIC FOOT (FEET)	SC	SHADING COEFFICIENT
PD	PRESSURE DROP	SCFM	STANDARD CUBIC FEET PER MINUTE
PEF	PROPELLER (TYPE) EXHAUST FAN	SCI	SPINAL CODE INJURY
PF	PRE-FILTER	SCR	SILICON CONTROLLED RECTIFIER
PG	PRESSURE GAGE	SD	SMOKE DETECTOR
PGW	PROPYLENE GLYCOL-WATER (SOLUTION)	SD	SUPPLY AIR DIFFUSER
PHC	PREHEAT COIL	SD-1	SCHEMATIC DESIGN (SUBMISSION1)
PPM	PARTS PER MILLION	SD-2	SCHEMATIC DESIGN (SUBMISSION2)
PRS	PRESSURE REGULATING (VALVE) STATION	SDPR	SMOKE DAMPER
PRV	PRESSURE REGULATING VALVE	SDR	SMOKE DAMPER (RETURN)
PSI	POUNDS PER SQUARE INCH	SDS	SMOKE DAMPER (SUPPLY)
PSIA	POUNDS PER SQUARE INCH - ABSOLUTE	SEN	SENSIBLE HEAT
PSIG	POUNDS PER SQUARE INCH - GAGE	SF	SUPPLY FAN
PSS	PRIMARY SECONDARY SYSTEM	SG	SUPPLY AIR GRILLE
PSV	PRESSURE SAFETY VALVE	SH	STEAM HUMIDIFIER
PTAC	PACKAGED TERMINAL AIR CONDITIONER	SHC	STEAM HEATING COIL
		SI	SQUARE INCHES
		SP	STATIC PRESSURE
R/E	RETURN OR EXHAUST	SP GR	SPECIFIC GRAVITY
RA	RETURN AIR	SPD	SUPPLY PROCESS AND DISTRIBUTION
RAD	RETURN AIR DAMPER	SPRV	STEAM PRESSURE REDUCING VALVE
RAF	RADIO FREQUENCY	SPS	STATIC PRESSURE SENSOR
RAHX	ROTARY AIR HEAT EXCHANGER	SQ FT	SQUARE FOOT (FEET)
RAT	RETURN AIR TEMPERATURE	SR	SUPPLY AIR REGISTER
RCCH	REMOTE CONDENSER CHILLER	SS	STAINLESS STEEL
RCU	RECIPROCATING CHILLER UNIT	SSHX	STEAM TO STEAM HEAT EXCHANGER
RD	REFRIGERANT DISCHARGE	SSR	SOLID SEPARATOR
RDS	ROOM DATA SHEETS	ST	STEAM TRAP
REA	RELIEF AIR	SUH	STEAM UNIT HEATER
RELAD	RELIEF AIR DAMPER	SV	STEAM PRESSURE REDUCING VALVE
RF	RETURN FAN	SVS	STEAM VENT SILENCER
RG	RETURN GRILLE	SW	SOFTWARE
RH	RELATIVE HUMIDITY	SWHX	STEAM TO WATER HEAT EXCHANGER
RHC	REHEAT COIL		
RHG	REFRIGERANT HOT GAS	T&PCV	TEMPERATURE AND PRESSURE
RL	REFRIGERANT LIQUID LINE		CONTROL VALVE
RLA	RUN LOAD AMPERE	TAB	TESTING, ADJUSTING, BALANCE
RO	REVERSE OSMOSIS	TD	TEMPERATURE DIFFERENCE
RPM	REVOLUTIONS PER MINUTE	TDH	TOTAL DYNAMIC HEAD
RR	RETURN REGISTER	TDS	TOTAL DISSOLVED SOLIDS
RS	REFRIGERANT SUCTION	TG	TRANSFER GRILLE
RTU	ROOF TOP UNIT	TP	TRAP
RV	RELIEF VALVE	TR	TOP REGISTER
		TSP	TOTAL STATIC PRESSURE
		TSTAT	THERMOSTAT
		TU	TERMINAL UNIT
		TWU	THRU-WALL UNIT



Department of  
Veterans Affairs

DETAIL TITLE: ABBREVIATIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-06.DWG

## ABBREVIATIONS

UC	UNDER CUT
UC	UNIT COOLER
UH	UNIT HEATER
U	UNDERWRITERS LABORATORY
URV	UPBLAST UNIT VENTILATOR
V	VALVE
VAF	VANE-AXIAL FAN
VAV	VARIABLE AIR VOLUME
VD	VOLUME DAMPER (MANUAL OPPOSED BLADE)
VFD	VARIABLE FREQUENCY DRIVE
VHA	VETERANS HEALTH ADMINISTRATION
VI	VIBRATION ISOLATOR
VP	VACUUM PUMP
VPS	VARIABLE PRIMARY SYSTEM
VR	VACUUM (STEAM CONDENSATE) RETURN
VSD	VARIABLE SPEED DRIVE
VUH	VERTICAL UNIT HEATER
W	WATTS
WAG	WASTE ANESTHESIA GAS
Wb	WET-BULB (TEMPERATURE)
WC	WATER COOLED
WCCH	WATER COOLED CHILLER
WCCU	WATER COOLED CONDENSING UNIT
WCHP	WATER COOLED HEAT PUMPS
WCPU	WATER COOLED PACKAGED UNIT
WEF	WALL EXHAUST FAN
WF	WATER FILTER
WFCV	WATER FLOW CONTROL VALVE
WFM	WATER FLOWMETER
WFMD	WATER FLOW MEASURING DEVICE
WG	WATER GAGE
WPD	WATER SIDE PRESSURE DROP
YR	YEAR



Department of  
Veterans Affairs





DETAIL TITLE: ABBREVIATIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-07.DWG

## DRAWING SYMBOLS



Department of  
Veterans Affairs

DETAIL TITLE / DRAWING SYMBOLS





















SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-08.DWG



# DUCTWORK SYMBOLS

	UP		DN	SUPPLY DUCT (UP & DOWN)
	UP		DN	EXHAUST DUCT (UP & DOWN)
	UP		DN	RETURN DUCT (UP & DOWN)
				ROUND AND SQUARE 4-WAY CEILING DIFFUSERS
				SQUARE 3-WAY CEILING DIFFUSERS
				SQUARE 2-WAY CEILING DIFFUSERS
				SQUARE 1-WAY CEILING DIFFUSERS
				LINEAR SLOT DIFFUSER
				SUPPLY TOP REGISTER OR GRILLE (WALL TYPE)
				EXHAUST OR RETURN CEILING REGISTER OR GRILLE
				EXHAUST OR RETURN BOTTOM REGISTER OR GRILLE (WALL TYPE)
				EXHAUST OR RETURN REGISTER OR TOP GRILLE (WALL TYPE)
				VANED ELBOW & AIR SPLIT TYPE DUCT TAKE-OFF
				CONNECT NEW DUCT TO EXISTING DUCT
				INCLINED RISE, IN DIRECTION OF AIR FLOW
				INCLINED DROP, IN DIRECTION OF AIR FLOW
				LIMIT OF DEMOLITION



Department of  
Veterans Affairs


DETAIL TITLE / DUCTWORK SYMBOLS

SCALE :NONE


DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-09.DWG


# DUCTWORK SYMBOLS




FLEXIBLE CONNECTION, EQUIPMENT,  
VIBRATION, OR SEISMIC




VANED ELBOW (PROVIDE ALL SQUARE OR  
RECTANGULAR ELBOWS WITH VANES EVEN IF  
SYMBOL IS MISSING)




VANED ELBOW (SHORT RADIUS)




STANDARD RADIUS ELBOW (LONG RADIUS)



NEW DUCT (INSIDE DIMENSIONS: WIDTH x DEPTH)




EXISTING DUCT TO REMAIN




EXISTING DUCT TO BE REMOVED




LOUVER (LOUVER SPECIFIED IN ARCHITECTURAL  
SECTION.)




FLEXIBLE DUCTWORK (INSULATED)




DUCT WITH SOUND LINING



MANUAL VOLUME DAMPER



FIRE DAMPER



BACK DRAFT DAMPER



Department of  
Veterans Affairs


DETAIL TITLE / DUCTWORK SYMBOLS

SCALE :NONE


DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-10.DWG


# DUCTWORK SYMBOLS




//FIRE//SMOKE// DAMPER  
(VA DOES NOT ALLOW COMBINATION FIRE/SMOKE DAMPERS.)




POINT OF CHANGE IN DUCT CONSTRUCTION BY STATIC PRESSURE CLASS. THE NUMBER ASSIGNS PRESSURE CLASS (IN. OF WATER) WHICH WILL ACCOMMODATE MAXIMUM OPERATING PRESSURE IN THE DUCT SUBSECTION. THE SYMBOL CONTINUES THE ASSIGNMENT UNTIL THE DUCT TERMINATES OR ANOTHER SYMBOL APPEARS. A "N" SUPERScript INDICATES NEGATIVE PRESSURE.




AUTOMATIC CONTROL DAMPER MODULATING




AUTOMATIC CONTROL DAMPER TWO POSITION





STAINLESS STEEL DUCT




MANUAL SPLITTER DAMPER



STANDARD BRANCH SUPPLY OR RETURN, NO SPLITTER (45° TAP)



DUCT MOUNTED COIL (HOT WATER OR STEAM COIL)



DUCT MOUNTED COIL (ELECTRIC)



Department of  
Veterans Affairs


DETAIL TITLE: DUCTWORK SYMBOLS

SCALE :NONE


DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-11.DWG


# TERMINAL UNIT SYMBOLS




CONVECTOR OR RADIATOR (RECESSED)




CONVECTOR OR RADIATOR (WALL HUNG)




FLOOR MOUNTED VERTICAL RECESSED FAN COIL UNIT.  
LETTER INDICATES UNIT SIZE.




FLOOR MOUNTED VERTICAL CABINET FAN COIL UNIT.  
LETTER INDICATES UNIT SIZE.




THRU WALL AIR CONDITIONING UNIT.  
LETTER INDICATES UNIT SIZE.




WINDOW TYPE AIR CONDITIONING  
UNIT. LETTER INDICATES UNIT SIZE.




FLOOR MOUNTED HEAT PUMP. LETTER  
INDICATES UNIT SIZE.



AIR CURTAIN



UNIT HEATER (HORIZONTAL)



UNIT HEATER (VERTICAL)



2'x2' RADIANT CEILING PANEL



2'x4' RADIANT CEILING PANEL



Department of  
Veterans Affairs

DETAIL TITLE: TERMINAL UNIT SYMBOLS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-12.DWG


# AIR TERMINAL SYMBOLS



TERMINAL UNIT WITH REHEAT COIL



DOUBLE DUCT MIXING BOX.



FAN POWERED VARIABLE VOLUME  
TERMINAL UNIT WITH HEATING COIL.



Department of  
Veterans Affairs

DETAIL TITLE / AIR TERMINAL SYMBOLS

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-13.DWG

# PIPING SYMBOLS

—————S-60—————	HIGH PRESSURE STEAM (60 PSIG AND ABOVE)
- - - - -CR-60- - - - -	HIGH PRESSURE STEAM CONDENSATE RETURN
—————S-30—————	MEDIUM PRESSURE STEAM (16 PSIG THRU 59 PSIG)
- - - - -CR-30- - - - -	MEDIUM PRESSURE STEAM CONDENSATE RETURN
—————S-15—————	LOW PRESSURE STEAM (15 PSIG AND BELOW)
- - - - -CR-15- - - - -	LOW PRESSURE STEAM CONDENSATE RETURN
—————PC—————	CONDENSATE PUMP DISCHARGE
—————HWS—————	HOT WATER HEATING SUPPLY
- - - - -HWR- - - - -	HOT WATER HEATING RETURN
—————GHS—————	GLYCOL-WATER HEATING SUPPLY
- - - - -GHR- - - - -	GLYCOL-WATER HEATING RETURN
—————SWS—————	SOLAR WATER SUPPLY
- - - - -SWR- - - - -	SOLAR WATER RETURN
—————RL—————	REFRIGERANT LIQUID
—————RS—————	REFRIGERANT SUCTION
—————RHG—————	REFRIGERANT HOT GAS
—————CWS—————	CONDENSER WATER SUPPLY (FROM TOWER)
- - - - -CWR- - - - -	CONDENSER WATER RETURN (TO TOWER)
—————CHS—————	CHILLED WATER SUPPLY
- - - - -CHR- - - - -	CHILLED WATER RETURN
—————GCS—————	CHILLED GLYCOL-WATER SUPPLY
- - - - -GCR- - - - -	CHILLED GLYCOL-WATER RETURN
—————MW—————	MAKE-UP WATER
—————D—————	DRAIN LINE
—————V—————	VENT LINE
—————GRS—————	GLYCOL-WATER RUN AROUND SUPPLY
- - - - -GRR- - - - -	GLYCOL-WATER RUN AROUND RETURN
—————X—————	EXISTING PIPE TO BE REMOVED



# PIPING SYMBOLS

————— FWPD —————	FEEDWATER PUMP DISCHARGE
————— FWPS —————	FEEDWATER PUMP SUCTION
————— CTPD —————	CONDENSATE TRANSFER PUMP DISCHARGE
————— CTPS —————	CONDENSATE TRANSFER PUMP SUCTION
————— VR —————	VACUUM CONDENSATE RETURN
————— TC —————	TUBE CLEANER WATER SUPPLY
————— BO —————	BOILER BLOWOFF
————— CBD —————	CONTINUOUS BLOWDOWN
————— BWS —————	BOILER WATER SAMPLE
————— FWS —————	FEEDWATER SAMPLE (FROM DEAERATOR)
————— CF —————	CHEMICAL FEED
————— OFL —————	OVERFLOW
————— A —————	COMPRESSED AIR
————— G —————	NATURAL GAS MAIN FUEL
————— G(I) —————	NATURAL GAS IGNITER FUEL
————— LPG(I) —————	LIQUEFIED PETROLEUM GAS IGNITER FUEL
————— FOS —————	FUEL OIL SUPPLY
————— FOR —————	FUEL OIL RETURN
————— CW —————	COLD WATER (CITY WATER)
————— SW —————	SOFTENED WATER
————— HW —————	HOT WATER
————— RH —————	ROLLER-TYPE HANGER
————— SH —————	VARIABLE SPRING-TYPE HANGER (TYPE 51)*
————— SCH —————	SPRING CUSHION-TYPE HANGER (TYPE 48 OR 49)*
————— ■ —————	CLEVIS-TYPE HANGER
————— TH —————	TRAPEZE HANGER (PROVIDE U-BOLT PIPE ATTACHMENT TO TRAPEZE EXCEPT WHERE RH ARE INDICATED)
————— PS —————	FLOOR-SUPPORTED PIPE STAND
————— RC —————	RISER CLAMP (TYPE 42)*
————— ○ —————	
————— WB —————	WALL BRACKET (TYPE 31, 32, 33)*
————— ■ —————	
————— CSH —————	CONSTANT SUPPORT HANGER (TYPE 54, 55, 56)*
————— ■ —————	
————— SS —————	SLIDING SUPPORTS (TYPE 35)*

\* TYPE NUMBERS REFER TO MANUFACTURER'S STANDARDIZATION SOCIETY STANDARD PRACTICE SP-58



Department of  
Veterans Affairs

























DETAIL TITLE: PIPING SYMBOLS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-15.DWG

# GENERAL PIPING SYMBOLS

	DIRECTION OF PIPE PITCH (DOWN)
	DIRECTION OF FLOW
	ANCHOR
	REDUCER OR INCREASER
	ECCENTRIC REDUCER
	TOP CONNECTION, 45° OR 90°
	BOTTOM CONNECTION, 45° OR 90°
	SIDE CONNECTION
	CAPPED OUTLET
	RISE OR DROP IN PIPE
	UNION
	PIPE UP
	PIPE DOWN
	INVERTED BUCKET TRAP SET INCLUDING PIPING ACCESSORIES SEE DETAIL
	FLOAT & THERMOSTATIC TRAP SET INCLUDING PIPING ACCESSORIES SEE DETAIL
	THERMOSTATIC TRAP SET INCLUDING PIPING ACCESSORIES SEE DETAIL
	THERMOMETER
	PRESSURE GAGE
	VENTURI FLOW METER
	REFRIGERANT SIGHT GLASS
	TEST PLUG (PRESSURE/TEMPERATURE)
	AUTOMATIC AIR VENT
	MANUAL AIR VENT
	QUICK-COUPLE HOSE CONNECTOR



Department of  
Veterans Affairs

DETAIL TITLE: GENERAL SYMBOLS



























SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-16.DWG



# VALVE SYMBOLS

	GATE VALVE – THREADED/FLANGED
	GLOBE VALVE – THREADED/FLANGED
	GATE VALVE WITH 3/4" HOSE ADAPTER
	CHECK VALVE
	WYE STRAINER (WITH BALL VALVE & HOSE CONNECTION)
	WYE STRAINER WITH VALVED DRAIN AND QUICK-COUPLE HOSE CONNECTOR
	FLEXIBLE CONNECTION
	ANGLE GLOBE VALVE
	BUTTERFLY VALVE
	BALL VALVE
	MODULATING CONTROL VALVE
	MODULATING CONTROL BUTTERFLY VALVE
	TWO POSITION CONTROL VALVE
	THREE-WAY MODULATING CONTROL VALVE
	THREE-WAY TWO POSITION CONTROL VALVE
	PRESSURE REGULATING VALVE
	PRESSURE SAFETY VALVE
	AUTOMATIC BALANCING CONTROL VALVE
	WATER BALANCE DEVICE
	CIRCUIT SETTER VALVE
	GATE VALVE WITH GLOBE-VALVED BYPASS
	PLUG VALVE
	CONTROL VALVE (CV) – FLOAT-OPERATED
	PRESSURE REDUCING VALVE (PRV)
	WATER LEVEL CONTROLLER
	FLOW METER



Department of  
Veterans Affairs





















DETAIL TITLE: VALVE SYMBOLS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-17.DWG

## CONTROLS SYMBOLS

	ROOM THERMOSTAT/TRANSMITTER – WALL MOUNT
	ROOM HUMIDISTAT (MOISTURE)/TRANSMITTER – WALL MOUNT
	TEMPERATURE TRANSMITTER
	TEMPERATURE TRANSMITTER, AVERAGING ELEMENT
	MOISTURE (HUMIDITY) TRANSMITTER
	PRESSURE TRANSMITTER
	STATIC PRESSURE SENSOR
	FLOW TRANSMITTER
	CURRENT TRANSMITTER
	CONDUCTIVITY TRANSMITTER
	SMOKE DETECTOR
	PRESSURE DIFFERENTIAL TRANSMITTER
	PRESSURE DIFFERENTIAL SWITCH
	HAND SWITCH (HAND-OFF-AUTO SWITCH)
	VALVE OR DAMPER POSITION CONTROLLER
	LOCAL RECORDING TIME CLOCK (RUNTIME)
	TEMPERATURE SWITCH, LOW (FREEZESTAT)
	TEMPERATURE SWITCH, HIGH (FREEZESTAT)
	LEVEL CONTROLLER
	LEVEL TRANSMITTER



Department of  
Veterans Affairs


















DETAIL TITLE / CONTROLS SYMBOLS

SCALE :NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230511-18.DWG

# CONTROLS SYMBOLS

	PRESSURE SWITCH HIGH
	PRESSURE SWITCH LOW
	ELECTRONIC TO PNEUMATIC TRANSDUCER
	CARBON DIOXIDE TRANSMITTER
	CARBON MONOXIDE TRANSMITTER
	OCCUPANCY SENSOR
	LOCAL TEMPERATURE CONTROL PANEL
	HVAC CONTROL PANEL
	VARIABLE SPEED MOTOR CONTROLLER
	INTEGRATE CONTROL POINT ON REMOTE GRAPHICS WORKSTATION AT ENERGY CONTROL CENTER
	TEMPERATURE CONTROLLER. SEE SEQUENCE OF OPERATION
	PRESSURE CONTROLLER. SEE SEQUENCE OF OPERATION
	SPEED CONTROLLER. SEE SEQUENCE OF OPERATION
	FLOW CONTROLLER. SEE SEQUENCE OF OPERATION
	FLOW SWITCH HIGH
	FLOW SWITCH LOW
	TIME CLOCK CONTROLLING EQUIPMENT ON A SCHEDULE



Department of  
Veterans Affairs


DETAIL TITLE / CONTROLS SYMBOLS

SCALE :NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230511-19.DWG

# CONTROLS SYMBOLS




TEMPERATURE SENSING ELEMENT FOR TRANSMITTING TEMPERATURE TO EMCS (PROVIDE 12 INCHES [200mm] MINIMUM LENGTH IN DUCT WHEN SPACE PERMITS.)



SENSOR WITH AVERAGING ELEMENT TO TRANSMIT TEMPERATURE TO EMCS



MOTOR STARTER



ELECTRIC OPERATED CONTROL DAMPER/OR VALVE




Department of  
Veterans Affairs

DETAIL TITLE / CONTROLS SYMBOLS

SCALE :NONE


DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230511-20.DWG




**DESIGNER'S NOTE:**  
SHOW ON THE DRAWINGS OTHER SPECIFIED AND SPECIAL PIPE SUPPORTS WHERE REQUIRED.

**NOTES:**  
SEE SPECIFER FOR DETAILED HANGER REQUIREMENTS




MAXIMUM PIPE/TUBING SUPPORT SPACING																			
NOM. SIZE	mm [IN]	THRU 20 [THRU 3/4]	25 [1]	32 [1 1/4]	40 [1 1/2]	50 [2]	65 [2 1/2]	75 [3]	100 [4]	125 [5]	150 [6]	200 [8]	250 [10]	300 [12]	350 [14]	400 [16]	450 [18]	500 [20]	600 [24]
PIPE	mm [FT]	2100 [7]	2100 [7]	2100 [7]	2700 [9]	3000 [10]	3400 [11]	3700 [12]	4100 [14]	4900 [16]	5200 [17]	5800 [19]	6700 [22]	7000 [23]	7600 [25]	8200 [27]	8500 [28]	9100 [30]	9600 [32]
TUBING	mm [FT]	1500 [5]	1800 [6]	2100 [7]	2400 [8]	2400 [8]	2700 [9]	3000 [10]	3700 [12]	4000 [13]	4100 [14]	4900 [16]	-	-	-	-	-	-	-

NOTE: FOR TRAPEZE HANGER TAKE SPACING OF SMALLEST SIZE ON TRAPEZE.




# PIPE HANGERS

NTS



**NOTES:**  
 PROVIDE RESTRAINING CLAMPS 2438mm [8'-0"] O.C.



# DETAIL FOR SUPPORTING PIPE ON ROOF

NTS



Department of  
 Veterans Affairs


DETAIL TITLE: DETAIL FOR SUPPORTING PIPE ON ROOF

SCALE :NONE


DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-22.DWG

PIPE ANCHOR SCHEDULE										
D		P		C		N		S		BOLT PATTERN
mm	in	mm	in	mm	in	mm	in	mm	in	
102	4	16	5/8	19	3/4	102	4	19	3/4	
76	3	13	1/2	13	1/2	102	4	16	5/8	
64	2 1/2	10	3/8	10	3/8	102	4	16	5/8	
51	2	10	3/8	10	3/8	102	4	16	5/8	
38	1 1/2	10	3/8	6	1/4	102	4	13	1/2"	



NOTE:  
WHERE USED FOR COPPER TUBE OR PIPE, BRAZE TO FABRICATED STEEL ANCHOR



## SMALL PIPE ANCHOR 38-102mm [1 1/2"-4"]

NTS










Department of  
Veterans Affairs


DETAIL TITLE: SMALL PIPE ANCHOR 38-104mm [1-1/2"-4"]

SCALE :NONE

DATE ISSUED: 11/01/2017


CAD DETAIL NO.: SD230511-23.DWG

PIPE ANCHOR SCHEDULE														BOLT PATTERN
D		L		P		T		E		N		S		
mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	
152	6	216	8½	19	¾	10	¾	6	¼	102	4	22	⅞	
203	8	254	10	19	¾	13	½	6	¼	102	4	22	⅞	
254	10	305	12	19	¾	13	½	6	¼	102	4	22	⅞	
305	12	356	14	19	¾	13	½	6	¼	102	4	22	⅞	
356	14	406	16	19	¾	13	½	13	½	102	4	22	⅞	
406	16	457	18	19	¾	13	½	13	½	102	4	22	⅞	
457	18	508	20	25	1	13	⅝	13	½	152	6	25	1	



**NOTES:**

- A. INSTALL WALL PLATE FIRST THEN WELD ON REMAINING ASSEMBLY. ONE WALL PLATE FOR BOTH CHILLED WATER S.&R. IS OPTIONAL.



NTS

## LARGE PIPE ANCHOR 152-457mm [6" -18"]



Department of  
Veterans Affairs

DETAIL TITLE: LARGE PIPE ANCHOR 152-457mm [6"-18"]

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-24.DWG





**NOTES:**

1. PROVIDE ANCHORS ONLY WHERE SHOWN ON DRAWINGS.
2. EXTEND SLEEVE ABOVE FLOOR WHERE SPECIFIED.

**DESIGNER'S NOTE:**

SHOW REQUIRED ANCHORS ON PLAN, SECTIONS OR DIAGRAMS.



# SUPPORT/ANCHOR FOR PIPE RISERS

NTS




Department of  
Veterans Affairs

DETAIL TITLE: SUPPORT/ANCHOR FOR PIPE RISERS


SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230511-25.DWG



## SUPPORT ANCHOR (CONDENSER WATER OR CHILLED WATER)



NTS



Department of  
Veterans Affairs

DETAIL TITLE / SUPPORT ANCHOR (CONDENSER WATER  
OR CHILLED WATER)

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-26.DWG




Department of  
Veterans Affairs

DETAIL TITLE / PIPE TRENCH IN BUILDING

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230511-27.DWG



NOTES:

1. COORDINATE TRENCH DETAIL WITH ARCHITECTURAL & STRUCTURAL.


2. REFER TO SPECIFICATION, SEALING & CAULKING.

# PIPE TRENCH IN BUILDING

NTS

#


DESIGNER'S NOTE:  
COORDINATE TRENCH DETAIL WITH ARCHITECTURAL & STRUCTURAL.



SCHEDULE		
SIZE OF PIPE INCH [mm]	SIZE OF "U" BOLT INCH [mm]	SIZE OF CHANNEL INCH [mm]
1 - 2 [25 - 50]	3/8 [10] DIA.	6 x 10.5 [150x265]
2-1/2 - 5 [65 - 125]	1/2 [15] DIA.	8 x 13.75 [200x345]
6 - 8 [150 - 200]	3/4 [20] DIA.	10 x 20 [250x500]

SCHEDULE FOR 8 FT. [2.4m] SPAN OR LESS.

## ANCHOR INSTALLATION STEAM/CONDENSATE PIPING IN TRENCH



NTS




Department of  
Veterans Affairs

DETAIL TITLE / ANCHOR INSTALLATION -  
STEAM/CONDENSATE PIPING IN TRENCH

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230511-28.DWG



**DETAIL "A"**  
(STEEL PIPE FOR WATER/GLYCOL)


**NOTE:**

1. SEISMIC SEPARATION ASSEMBLY DETAIL SHOWN IN NFPA 13 (SPRINKLER PIPING), UTILIZING FLEXIBLE MECHANICAL COUPLINGS, MAY BE USED IN LIEU OF PIPING DETAIL SHOW ABOVE.

SCHEDULE FOR PIPING CROSSING  
A SEISMIC JOINT

LOCATION	PIPE	DETAIL	DIMENSIONS INCHES [mm]					
			a	b	c	d	e	f
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

## PIPING CROSSING A SEISMIC JOINT DETAIL "A"



NTS

DESIGNER'S NOTE:

1. THIS CONFIGURATION SHOWN IN THIS DETAIL IS A SUGGESTED ARRANGEMENT, NOT MANDATED FOR USE IN AS IS CONDITION. THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER IN CHARGE OF THE PROJECT SHALL PROVIDE SEISMIC CALCULATIONS AND MODIFY THE CONFIGURATION AS NEEDED TO MAKE THE ARRANGEMENT PROJECT-SPECIFIC. THE MECHANICAL DESIGNER SHALL COMPLETE THE BLANK SCHEDULES BY INSERTING THE DISTANCES, TO BE CALCULATED AND FURNISHED BY PROVIDED BY THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER.




Department of  
Veterans Affairs

DETAIL TITLE / PIPING CROSSING A SEISMIC JOINT  
DETAIL "A"

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230511-29.DWG



DETAIL "B"

(PLASTIC PIPE FOR PRESSURIZED SYSTEMS)

## SCHEDULE FOR PIPING CROSSING A SEISMIC JOINT

LOCATION	PIPE	DETAIL	DIMENSIONS INCHES [mm]			
			a	b	c	d
-	-	-	-	-	-	-
-	-	-	-	-	-	-

## PIPING CROSSING A SEISMIC JOINT

### DETAIL "B"

#

NTS

DESIGNER'S NOTE:

1. THIS CONFIGURATION SHOWN IN THIS DETAIL IS A SUGGESTED ARRANGEMENT, NOT MANDATED FOR USE IN AS IS CONDITION. THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER IN CHARGE OF THE PROJECT SHALL PROVIDE SEISMIC CALCULATIONS AND MODIFY THE CONFIGURATION AS NEEDED TO MAKE THE ARRANGEMENT PROJECT-SPECIFIC. THE MECHANICAL DESIGNER SHALL COMPLETE THE BLANK SCHEDULES BY INSERTING THE DISTANCES, TO BE CALCULATED AND FURNISHED BY PROVIDED BY THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER.





Department of  
Veterans Affairs

DETAIL TITLE / PIPING CROSSING A SEISMIC JOINT  
DETAIL "B"

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230511-30.DWG



SCHEDULE FOR PIPING CROSSING  
A SEISMIC JOINT

LOCATION	PIPE	DETAIL	DIMENSIONS INCHES [mm]				
			a	b	c	d	e
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

# **PIPING CROSSING A SEISMIC JOINT DETAIL "C"**  
NTS

DESIGNER'S NOTE:

1. THIS CONFIGURATION SHOWN IN THIS DETAIL IS A SUGGESTED ARRANGEMENT, NOT MANDATED FOR USE IN AS IS CONDITION. THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER IN CHARGE OF THE PROJECT SHALL PROVIDE SEISMIC CALCULATIONS AND MODIFY THE CONFIGURATION AS NEEDED TO MAKE THE ARRANGEMENT PROJECT-SPECIFIC. THE MECHANICAL DESIGNER SHALL COMPLETE THE BLANK SCHEDULES BY INSERTING THE DISTANCES, TO BE CALCULATED AND FURNISHED BY PROVIDED BY THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER.




Department of  
Veterans Affairs

DETAIL TITLE / PIPING CROSSING A SEISMIC JOINT  
DETAIL "C"

SCALE :NONE

DATE ISSUED :DECEMBER 2008


CADD DETAIL NO. : SD230511-31.DWG



(STEEL PIPE FOR STEAM OR WATER)

SCHEDULE FOR PIPING CROSSING A SEISMIC JOINT						
LOCATION	PIPE	DETAIL	DIMENSIONS INCHES [mm]			
			a	b	c	d
-	-	-	-	-	-	-
-	-	-	-	-	-	-

## PIPING CROSSING A SEISMIC JOINT DETAIL "D"



NTS

DESIGNER'S NOTE:

1. THIS CONFIGURATION SHOWN IN THIS DETAIL IS A SUGGESTED ARRANGEMENT, NOT MANDATED FOR USE IN AS IS CONDITION. THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER IN CHARGE OF THE PROJECT SHALL PROVIDE SEISMIC CALCULATIONS AND MODIFY THE CONFIGURATION AS NEEDED TO MAKE THE ARRANGEMENT PROJECT-SPECIFIC. THE MECHANICAL DESIGNER SHALL COMPLETE THE BLANK SCHEDULES BY INSERTING THE DISTANCES, TO BE CALCULATED AND FURNISHED BY PROVIDED BY THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER.



Department of  
Veterans Affairs


DETAIL TITLE / PIPING CROSSING A SEISMIC JOINT  
DETAIL "D"

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230511-32.DWG






DETAIL "E"  
(STEEL PIPE FOR WATER)

SCHEDULE FOR PIPING CROSSING A SEISMIC JOINT								
LOCATION	PIPE	DETAIL	DIMENSIONS INCHES [mm]					
			a	b	c	d	e	f
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

## PIPING CROSSING A SEISMIC JOINT DETAIL "E"



NTS

### DESIGNER'S NOTE:

1. THIS CONFIGURATION SHOWN IN THIS DETAIL IS A SUGGESTED ARRANGEMENT, NOT MANDATED FOR USE IN AS IS CONDITION. THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER IN CHARGE OF THE PROJECT SHALL PROVIDE SEISMIC CALCULATIONS AND MODIFY THE CONFIGURATION AS NEEDED TO MAKE THE ARRANGEMENT PROJECT-SPECIFIC. THE MECHANICAL DESIGNER SHALL COMPLETE THE BLANK SCHEDULES BY INSERTING THE DISTANCES, TO BE CALCULATED AND FURNISHED BY PROVIDED BY THE REGISTERED PROFESSIONAL STRUCTURAL ENGINEER.




Department of  
Veterans Affairs

DETAIL TITLE / PIPING CROSSING A SEISMIC JOINT  
DETAIL "E"

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230511-33.DWG



ISOMETRIC VIEW

TABLE OF FORCES AND MOMENTS DUE TO THERMAL EXPANSION AND WEIGHT OF STEAM LEAD AND VALVES

BOILER NO.	Fx LB [Kg]	Fy LB [Kg]	Fz LB [Kg]	Mx FT LB [J]	My FT LB [J]	Mz FT LB [J]
-----	--[---]	--[---]	--[---]	--[---]	--[---]	--[---]


TABLE OF FORCES AND MOMENTS DUE TO SEISMIC ACTION OF THE STEAM LEAD AND VALVES

BOILER NO.	Fx LB [Kg]	Fy LB [Kg]	Fz LB [Kg]	Mx FT LB [J]	My FT LB [J]	Mz FT LB [J]
-----	--[---]	--[---]	--[---]	--[---]	--[---]	--[---]

NOTES:

1. BOILERS SHALL BE DESIGNED TO WITHSTAND THE FORCES AND MOMENTS SHOWN ABOVE.
2. ADD ANY Fy FORCE (500 LB [230 Kg] MINIMUM) AS AN ESTIMATION OF THE WEIGHT EFFECT OF THE STEAM LEAD AND VALVE ON THE BOILER. BOILER AND PIPE HANGER SUPPLIERS SHALL COORDINATE TO DETERMINE THE EXACT Fy FORCE WHICH WILL BE IMPOSED ON THE STEAM NOZZLES.
3. DELETE THE SEISMIC TABLE ON NON-SEISMIC AREAS.

# FORCES AND MOMENTS ON BOILER STEAM NOZZLES



NTS




Department of Veterans Affairs

DETAIL TITLE / FORCES AND MOMENTS ON BOILER STEAM NOZZLES


SCALE :NONE

DATE ISSUED :FEBRUARY 2008


CADD DETAIL NO. : SD230511-34.DWG




TYPE "B"  
WELDED STEEL BASE



SECTION A-A



TYPE "1"  
CONCRETE INERTIA BASE



# VIBRATION ISOLATION BASES

NTS




Department of  
Veterans Affairs

DETAIL TITLE / VIBRATION ISOLATION BASES

SCALE : NONE


DATE ISSUED : DECEMBER 2008

CADD DETAIL NO. : SD230541-01.DWG



NOTES:

1. ATTACH THRUST RESTRAINTS SYMMETRICALLY ON BOTH SIDES OF THE FAN DISCHARGE.
2. ADJUST RESTRAINT TO ALLOW 1/4" [6 mm] MOVEMENT OF FAN AT START AND STOP.



## THRUST RESTRAINT FOR FANS

NTS

DESIGNER'S NOTE:

ON THE VIBRATION ISOLATION SCHEDULE OR UNDER THE TITLE OF THIS DETAIL DESIGNATE FANS REQUIRING RESTRAINT. THIS IS USUALLY SEPARATELY MOUNTED FAN SECTIONS FOR STATIC PRESSURE OVER 4" [100 mm] AND POSSIBLY FOR AXIAL FLOW FANS FOR STATIC PRESSURE OVER 4" [100 mm].






Department of  
Veterans Affairs

DETAIL TITLE / THRUST RESTRAINT FOR FANS


SCALE :NONE

DATE ISSUED : DECEMBER 2008

CADD DETAIL NO. : SD230541-02.DWG



NOTE:  
L & W DIMENSIONS SHALL BE 6" [150mm] GREATER THAN THE EQUIPMENT BASE PLATE.



# CONCRETE EQUIPMENT BASES

NTS

**DESIGNER'S NOTE:**

THIS DETAIL IS PRIMARILY FOR PUMPS WITHOUT ISOLATORS. COORDINATE DETAIL WITH ARCHITECTURAL AND STRUCTURAL.



Department of  
Veterans Affairs

DETAIL TITLE / CONCRETE EQUIPMENT BASES

SCALE :NONE

DATE ISSUED : DECEMBER 2008

CADD DETAIL NO. : SD230541-03.DWG




Department of  
Veterans Affairs

DETAIL TITLE / SEISMIC BRACING FOR LIGHT SUSPENDED EQUIPMENT/  
EQUIPMENT RESTRAINED BY RESILIENT PADS (TYPE DS)

SCALE :NONE


DATE ISSUED : DECEMBER 2008

CADD DETAIL NO. : SD230541-04.DWG



SEISMIC BRACING FOR LIGHT  
SUSPENDED EQUIPMENT

NOTE:  
NOT REQUIRED FOR  
AIR TERMINAL UNITS.




FLOOR MOUNT EQUIPMENT  
RESTRAINED BY RESILIENT PADS  
(TYPE DS)

# SEISMIC BRACING FOR EQUIPMENT


#

NTS

STEEL EXPANSION SHIELD FOR EXISTING CONSTRUCTION AND INSERTS FOR NEW CONSTRUCTION THIS TYPE SHALL BE USED ONLY IN SLABS OR BEAMS OF 4" [100mm] MIN DEPTH



FOR PIPES UNDER 2" [50mm] IN SIZE USE 1 1/2"x1 1/2"x1/4" [40x40x6.4mm] ANGLE.  
 ALL PIPES 2" [50mm] & LARGER USE 3"x3"x1/4" [75x75x6.4mm] ANGLE



# SECURING HANGER RODS IN CONCRETE

NTS




Department of  
Veterans Affairs

DETAIL TITLE / SECURING HANGER RODS IN CONCRETE

SCALE :NONE

DATE ISSUED : DECEMBER 2008


CADD DETAIL NO. : SD230541-05.DWG



ELEVATION

NOTES:

1. INSTALLATION OF SENSORS AND TRANSMITTERS SHALL CONFORM TO RECOMMENDATIONS OF MANUFACTURERS OF TRANSMITTERS.



# PRESSURE TRANSMITTER INSTALLATION

NTS



Department of  
Veterans Affairs

DETAIL TITLE / PRESSURE TRANSMITTER INSTALLATION



SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.:

SD230911-01.DWG





# WATER METER INSTALLATION

NTS



Department of  
Veterans Affairs

DETAIL TITLE / WATER METER INSTALLATION

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD230911-02.DWG

LEGEND


ITEM NO.

DESCRIPTION


1. ALARM BELL (WATER LEVEL)
2. DRAFT GAUGES
  - A. WINDBOX (0 TO \_\_\_\_\_mm(\_\_\_\_IN) WC) (SEE NOTE 4)
  - B. FURNACE (0 TO \_\_\_\_\_mm(\_\_\_\_IN) WC) (SEE NOTE 4)
  - C. BOILER OUTLET (\_\_\_\_mm(\_\_\_\_IN) TO + \_\_\_\_\_mm(\_\_\_\_IN) WC) (SEE NOTE 5)
  - D. ECONOMIZER OUTLET (-25mm(-1") TO +25mm(+1") WC) (SEE NOTE 5)
3. ALARM HORN (FLAME FAILURE, LOW WATER CUTOFF)
4. BURNER CONTROL SYSTEM ANNUNCIATOR
5. ROW OF BURNER CYCLE PILOT-LIGHTS
6. ROW OF BURNER CONTROL SWITCHES
7. BOILER WATER LEVEL CONTROL STATION
8. ECONOMIZER TEMPERATURE INDICATOR
9. SELECTOR SWITCH FOR ECONOMIZER TEMPERATURE INDICATOR
10. BURNER STOP SWITCH

NOTES:

1. INTERIOR OF PANEL SHALL BE UTILIZED FOR MOUNTING RELAYS, BURNER CONTROL PROGRAMMER, AND OTHER DEVICES.
2. PROVIDE FRONT OR REAR ACCESS DOORS FULL HEIGHT AND WIDTH OF PANEL.
3. PANEL DIMENSIONS APPROX. 1M(3'-0")Wx0.5M(1'-6")Dx2.3M(7'-6")H.
4. WINDBOX AND FURNACE DRAFT GAGE SCALE RANGES RECOMMENDED BY BOILER AND BURNER MANUFACTURER.
5. SCALE RANGE OF BOILER OUTLET DRAFT GAGE MUST BE COORDINATED WITH ECONOMIZER DRAFT LOSS. IF THERE IS NO ECONOMIZER, RANGE SHOULD BE -25mm(-1") TO +25mm(+1") WC.
6. BOILER COMBUSTION CONTROL SUBMASTER, DRAFT CONTROL AND OXYGEN TRIM CONTROL STATIONS MAY BE LOCATED ON THIS PANEL.



# BURNER CONTROL PANEL FOR WATER TUBE BOILERS



NTS




Department of  
Veterans Affairs

DETAIL TITLE: BURNER CONTROL PANEL FOR  
WATER TUBE BOILERS

SCALE :NONE

DATE ISSUED :11/01/2017

CADD DETAIL NO. : SD230911-03.DWG



ELEVATION


**DESIGNER NOTES:**

1. PANEL APPROX. 3810mm[12'-6"]Wx610mm[2'-0"]Dx2438mm[8'-0"]H. SHOW ACTUAL SIZE ON DWGS.
2. SOME RECORDING & MONITORING FUNCTIONS MAY BE HANDLED BY A COMPUTER WORK STATION & THEREFORE MAY BE DELETED FROM THIS PANEL.
3. ON SOME PROJECTS, IT MAY BE DESIRABLE TO LOCATE EMERGENCY GENERATOR ANNUNCIATORS & METERS ON THIS PANEL.
4. PROVIDE SMOKE DENSITY MONITORS ONLY ON PLANTS BURNING HEATED OIL OR WHERE REQUIRED BY LOCAL CODES.
5. ON PLANTS WHERE DRAFT CONTROL SYSTEMS ARE PROVIDED, CONSIDER LOCATING THE DRAFT GAGES ON THIS PANEL ABOVE THE BOILER OPERATION RECORDERS. THE GAGES ARE NORMALLY LOCATED ON THE BURNER CONTROL PANELS.
6. DELETE THE "ENGINEERING NOTES" FROM THE PROJECT DRAWINGS.

**ITEM NO.**

**DESCRIPTION**

1. BOILER / BOILER PLANT DIGITAL DATA RECORDER
  - A. STEAM FLOW: INDICATE, RECORD, INTEGRATE, [0-\_\_\_\_\_ KG/S [LB/HR]]
  - B. BOILER OUTLET FLUE GAS TEMPERATURE: RECORD (0-500°C [0-1000°F])
  - C. FLUE GAS OXYGEN CONTENT: RECORD (0-10% OXYGEN)
  - D. HIGH PRESS STEAM DIST: RECORD, INTEGRATE, (0-\_\_\_\_\_ KG/S [LB/HR])
  - E. MED PRESS STEAM DIST: RECORD, INTEGRATE, (0-\_\_\_\_\_ KG/S [LB/HR])
  - F. LAUNDRY STEAM DIST: RECORD, INTEGRATE, (0-\_\_\_\_\_ KG/S [LB/HR])
  - G. BOILER PLANT STEAM: RECORD, INTEGRATE, (0-\_\_\_\_\_ KG/S [LB/HR])
  - H. STEAM HEADER PRESS: RECORD (0-2000 kPa [0-300 PSIG])
  - I. BOILER FEEDWATER TEMP: RECORD (0-150°C [0-300°F])
  - J. OUTSIDE AIR TEMP: RECORD (-35°C[-30°F] TO +50°C[+120°F])
2. BOILER CONTROL STATIONS (MANUAL/AUTOMATIC, BIAS)  
(THESE CONTROL STATIONS MAY BE LOCATED ON THE BURNER CONTROL PANELS INSTEAD OF ON THE INSTRUMENTATION PANEL.)
  - A. COMBUSTION CONTROL SUBMASTER
  - B. DRAFT CONTROL (WHEN SPECIFIED)
  - C. OXYGEN TRIM (WHEN SPECIFIED)
3. MASTER STEAM PRESSURE CONTROLLER
4. CLOCK
5. ALARM ANNUNCIATOR
  - A. CONDENSATE STORAGE TANK HIGH LEVEL
  - B. CONDENSATE STORAGE TANK LOW LEVEL
  - C. FEEDWATER HEATER HIGH LEVEL
  - D. FEEDWATER HEATER LOW LEVEL
  - E. HIGH STEAM HEADER PRESS
  - F. EMERGENCY GAS VALVE CLOSED
  - G. HIGH NATURAL GAS HEADER PRESS (SET AT 35 kPa [5 PSIG] ABOVE MAIN REGULATOR SET PRESS)
  - H. LP IGNITER GAS IN USE-FOR EMERGENCY ONLY (PROVIDE HIGH PRESS SWITCH SET AT 14 kPa [2 PSIG])
  - I. LOW EXCESS AIR BOILER NO. (PROVIDE ONE POINT FOR EACH BOILER, SET AT \_\_\_\_ % OXYGEN)
6. ANNUNCIATOR ACKNOWLEDGE BUTTON
7. ANNUNCIATOR TEST BUTTON
8. ANNUNCIATOR BELL / HORN
9. EMERGENCY GAS SAFETY SHUT OFF VALVE CONTROL
10. PRESSURE GAGES
  - A. STEAM HEADER (0-1500 kPa [0-200 PSIG])
  - B. NATURAL GAS HEADER (0-100 kPa [0-15 PSIG])
  - C. FUEL OIL HEADER (0-1500 kPa [0-200 PSIG])
  - D. BOILER FEEDWATER HEADER (0-2000 kPa [0-300 PSIG]) (WHEN HEADER SERVING ALL BOILERS IS PROVIDED)
11. START-STOP BUTTONS AND PILOT LIGHTS FOR PUMPS
12. SMOKE DENSITY MONITOR (WHEN SPECIFIED)
13. REMOTE REGISTER FOR GAS METER (WHEN SPECIFIED)
14. FEEDWATER DEAERATOR TANK AND CONDENSATE STORAGE TANK WATER LEVEL CONTROL STATION



**BOILER PLANT INSTRUMENTATION PANEL**


NTS

DETAIL TITLE: BOILER PLANT INSTRUMENTATION PANEL

SCALE : NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD230911-04.DWG



**GENERAL NOTES:**

1. MAINTAIN NEGATIVE AIR PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL]) BETWEEN THE AII ROOM AND THE ANTEROOM AND THE ANTEROOM AND THE CORRIDOR BY MODULATING VALVE V1. AII ROOMS SHALL HAVE A PERMANENTLY INSTALLED DEVICE AND/OR MECHANISM TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND THE CORRIDOR. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER NEGATIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED. (STROBE LIGHT)
2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE AII ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE EXHAUST AIR REGISTER OVER THE PATIENT BED ON THE CEILING. AS AN ALTERNATE, THE EXHAUST AIR REGISTER CAN BE LOCATED ON THE WALL NEAR THE PATIENT HEAD, IF FEASIBLE.
4. LOCATE THE SUPPLY AIR OUTLET TO BLOW AIR TOWARDS THE OCCUPIED AREA.
5. PROVIDE A DEDICATED EXHAUST SYSTEM FOR THE AII ROOMS WITHOUT MIXING IT WITH ANY OTHER EXHAUST.

**TYPICAL AIR BALANCE EXAMPLE:**

1. THE PATIENT BEDROOM IS KEPT UNDER NEGATIVE PRESSURE BY ENSURING AIR MOVEMENT INTO THE BEDROOM SPACE FROM THE ANTE ROOM AND ADJOINING CORRIDOR.
2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE AS FOLLOWS:
  - A - PATIENT BEDROOM MINIMUM 12 ACPH SUPPLY AIR (ASHRAE STANDARD 170 2008). INCREASE SUPPLY AIR VOLUME, IF REQUIRED, TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODES. EXAMPLE: 400 CFM [190 L/S]
  - B - ANTE ROOM MINIMUM 10 ACPH (ASHRAE STANDARD 170 2008) OR MINIMUM 40 CFM [19 L/S] SUPPLY + 100 CFM [47 L/S] INFILTRATED INTO ANTE ROOM FROM CORRIDOR FOR A TOTAL OF 140 CFM [66 L/S].
  - C - PATIENT TOILET DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28 L/S]. EXAMPLE: 60 CFM [28 L/S]
3. THE DEDICATED EXHAUST AIR SYSTEM SHALL BE BALANCED AS FOLLOWS:
  - A - PATIENT BEDROOM 400 CFM [190 L/S](SUPPLY) - 60 CFM [28 L/S](TOILET) + 40 CFM [19 L/S] SUPPLY AIR TO ANTE ROOM + 100 CFM [47 L/S] INFILTRATED FROM CORRIDOR INTO ANTE ROOM THEN 140 CFM [66 L/S] INTO AII ROOM = 480 CFM [227 L/S] (EXHAUST), TOTAL EXHAUST 540 CFM [255 L/S]
  - 4. COORDINATE DOOR UNDER CUTS FOR DOORS BETWEEN ANTE ROOM AND PATIENT (1") [2.54 CM], DOOR TO CORRIDOR.


**AIR SYSTEM FOR AIRBORNE INFECTION ISOLATION ROOM (AII)( WITH ANTE ROOM)**

#

NTS  
NEGATIVE PRESSURE

**DESIGNER'S NOTE:**

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.



**GENERAL NOTES:**

1. MAINTAIN NEGATIVE AIR PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL]) BETWEEN THE AII ROOM AND THE CORRIDOR BY MODULATING VALVE V1. AII ROOMS SHALL HAVE A PERMANENTLY INSTALLED DEVICE AND/OR MECHANISM TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND THE CORRIDOR. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER NEGATIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED. (STROBE LITE)
2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE AII ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE EXHAUST AIR REGISTER OVER THE PATIENT BED ON THE CEILING. AS AN ALTERNATE, THE EXHAUST AIR REGISTER CAN BE LOCATED ON THE WALL NEAR THE PATIENT HEAD, IF FEASIBLE.
4. LOCATE THE SUPPLY AIR OUTLET TO BLOW AIR TOWARDS THE OCCUPIED AREA.
5. PROVIDE A DEDICATED EXHAUST SYSTEM FOR THE AII ROOMS WITHOUT MIXING IT WITH ANY OTHER EXHAUST.

**TYPICAL AIR BALANCE EXAMPLE:**

1. THE PATIENT BEDROOM IS KEPT UNDER NEGATIVE PRESSURE BY ENSURING AIR MOVEMENT INTO THE BEDROOM SPACE FROM THE ADJOINING CORRIDOR.
2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE AS FOLLOWS:

- A – PATIENT BEDROOM  
MINIMUM 12 ACPH SUPPLY AIR (ASHRAE STANDARD 170 2008). INCREASE SUPPLY AIR VOLUME, IF REQUIRED, TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODES.  
EXAMPLE: 400 CFM [190 L/S]
- B – PATIENT TOILET  
DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28 L/S]. EXAMPLE: 60 CFM [28 L/S]

3. THE DEDICATED EXHAUST AIR SYSTEM SHALL BE BALANCED AS FOLLOWS:

- A – PATIENT BEDROOM  
400 CFM [190 L/S] (SUPPLY) – 60 CFM [28 L/S] (TOILET) + 100 CFM [47 L/S] INFILTRATED FROM CORRIDOR = 440 CFM [180 L/S] (EXHAUST), TOTAL EXHAUST 500 CFM [240 L/S].


#

NTS  
NEGATIVE PRESSURE

**DESIGNER'S NOTE:**

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.


## AIR SYSTEM FOR AIRBORNE INFECTIOUS ISOLATION ROOM (AII) (WITHOUT ANTEROOM)



SEQUENCE OF OPERATION:

WHEN FILTER PRESSURE DROP RISES TO 2" [7 KPA] OF WATER COLUMN, FILTER STATUS LIGHT (RED) SHALL BE ENERGIZED.

## HEPA FILTER CONTROLS FOR AUTOPSY EXHAUST SYSTEMS



NTS



Department of  
Veterans Affairs


DETAIL TITLE / HEPA FILTER CONTROLS FOR AUTOPSY  
EXHAUST SYSTEMS

SCALE :NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.:

SD230923-03.DWG



#

# VARIABLE AIR VOLUME AIR HANDLING UNIT WITH MINIMUM OUTSIDE AIR CONTROL DIAGRAM

NTS

DETAIL TITLE / VARIABLE AIR VOLUME AIR HANDLING UNIT WITH MINIMUM OUTSIDE AIR CONTROL DIAGRAM

SCALE : NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD230923-04.DWG

Department of Veterans Affairs



# SEQUENCE OF OPERATION FOR VARIABLE AIR VOLUME AIR HANDLING UNIT WITH MINIMUM OUTSIDE AIR

## 1. GENERAL

\_1.1 UNIT IS NORMALLY STARTED AND STOPPED REMOTELY AT THE ECC. H-0-A SWITCH SHALL BE KEPT IN THE "AUTO" POSITION. "HAND" AND "OFF" POSITIONS SHALL BE USED ONLY FOR MAINTENANCE. WHEN THE UNIT IS "OFF" D-1, D-3, SHALL BE FULLY CLOSED. WHEN THE UNIT IS "ON" D-1, SD-1 AND SD-2 SHALL BE FULLY OPEN. D-2 AND D-3 SHALL MODULATE IN ACCORDANCE WITH THE FOLLOWING SEQUENCE:

## 2. TEMPERATURE CONTROL

- \_2.1 SUPPLY AIR TEMPERATURE, SENSED BY TT-1, SHALL BE MAINTAINED AT SETPOINT VIA DIGITAL CONTROL PANEL BY MODULATING V-1 OR D-2 AND D-3 OR V-2 IN SEQUENCE.
- 2.2 WHEN THE TEMPERATURE OF THE OUTSIDE AIR, SENSED BY TT-2, IS ABOVE 75°F (ADJ) [23.8°C], THE DIGITAL CONTROL PANEL SHALL PREVENT THE MODULATION OF D-2 AND D-3 AND SHALL ASSUME THE MINIMUM OUTSIDE AIR POSITION (D-2 FULLY OPENED AND D-3 FULLY CLOSED). THE DIGITAL CONTROL PANEL SHALL MODULATE V-1 TO MAINTAIN THE SUPPLY AIR TEMPERATURE, SENSED BY TT-1.
- 2.3 WHEN THE TEMPERATURE OF THE OUTSIDE AIR, SENSED BY TT-2, IS BETWEEN 65°F [18.3°C] AND THE SUPPLY AIR TEMPERATURE SENSED BY TT-1, DAMPER D-2 SHALL FULLY CLOSE AND D1 AND D3 SHALL BE FULLY OPEN (MAXIMUM OUTSIDE AIR POSITION). THE DIGITAL CONTROL PANEL SHALL MODULATE V-1 TO MAINTAIN THE SUPPLY AIR TEMPERATURE, SENSED BY TT-1.
- 2.4 WHEN THE TEMPERATURE OF THE OUTSIDE AIR, SENSED BY TT-2, IS BELOW THE SUPPLY AIR TEMPERATURE, SENSED BY TT-1, DAMPERS D1, D-2 AND D-3 SHALL MODULATE TO MAINTAIN THE SCHEDULED SUPPLY AIR TEMPERATURE. IF D-2 IS OPEN AND D-3 IS CLOSED TO MINIMUM OUTSIDE AIR, V-2 SHALL MODULATE OPEN TO MAINTAIN THE SUPPLY AIR TEMPERATURE, SENSED BY TT-1.

## 3. AIR FLOW CONTROL

- \_3.1 THE SUPPLY AIR FLOW SHALL BE CONTROLLED BY THE DIGITAL CONTROL PANEL MODULATING THE SUPPLY FAN VARIABLE SPEED MOTOR CONTROLLER TO MAINTAIN 1.0" [25mm] OF DUCT STATIC PRESSURE (FIELD ADJUSTABLE), SENSED BY SPS-1. RESET STATIC PRESSURE BASED ON ACTUAL BUILDING LOAD BY POLLING ALL ATU
- 3.2 THE DIGITAL CONTROL PANEL, USING TOTAL SUPPLY AIR AND RETURN AIR FLOW SIGNALS, SHALL RESET THE RETURN AIR FAN VSMC TO MAINTAIN A CONSTANT AIR FLOW DIFFERENCE BETWEEN THE SUPPLY AIR AND THE RETURN AIR EQUAL TO MINIMUM OUTSIDE AIR.
- 3.3 USING HIGH PRESSURE SENSOR SPS-2 LOCATED AT THE SUPPLY FAN DISCHARGE, SHALL PREVENT THE SUPPLY FAN FROM DEVELOPING OVER 3" [75mm] OF STATIC PRESSURE (FIELD ADJUSTABLE). IF STATIC PRESSURE AT SPS-2 DOES EXCEED 3" [75mm] THE SUPPLY AIR FAN SHALL STOP. SPS-2 SHALL BE HARDWIRED TO THE SUPPLY FAN VSMC AND UNIT SHALL BE SHUTDOWN IN HAND,AUTO OR BYPASS MODE. SPS-2 WILL REQUIRE MANUAL RESET AT THE DEVICE.

## 4. HUMIDITY CONTROL

- \_4.1 WHEN THE DIGITAL CONTROL PANEL IS NOT CALLING FOR HUMIDITY, SENSED BY RETURN AIR HUMIDITY H-1, 2-WAY "ON-OFF" CONTROL VALVE V-3 SHALL REMAIN CLOSED. WHEN THE DIGITAL CONTROL PANEL IS CALLING FOR HUMIDITY, V-3 SHALL REMAIN OPEN.
- 4.2 RETURN AIR HUMIDITY SHALL BE MAINTAINED AT SETPOINT OF 35% RH (ADJ) VIA DIGITAL CONTROL PANEL BY MODULATING CONTROL VALVE V-4 TO MAINTAIN THE DESIRED HUMIDITY. THE DCP SHALL OVERRIDE THIS CONTROL TO MAINTAIN HUMIDITY OF 80% AS SENSED BY H-2. DCP SHALL CLOSE VALVE V-3 WHENEVER THE SUPPLY FAN IS OFF. VALVE V-4 SHALL BE INTERLOCKED WITH A TEMPERATURE SWITCH TO KEEP THE HUMIDIFIER OFF UNTIL CONDENSATE TEMPERATURE APPROACHES STEAM TEMPERATURE.

## 5. FREEZE PROTECTION

- \_5.1 IF THE AIR TEMPERATURE AS SENSED BY TT-3 FALLS BELOW 45°F [7°C], AN ALARM SIGNAL SHALL INDICATE AT THE DCP AND ECC. IF THIS TEMPERATURE FALLS BELOW 40°F [4.4°C], AS SENSED BY THE TSL THE SUPPLY AND RETURN FANS SHALL SHUT DOWN AND A CRITICAL ALARM SHALL INDICATE AT THE DIGITAL CONTROL PANEL AND ECC. TSL SHALL BE HARDWIRED TO THE SUPPLY FAN UFD AND UNIT SHALL BE SHUTDOWN IN HAND,AUTO OR BYPASS MODE. TSL WILL REQUIRE MANUAL RESET AT THE DEVICE.

## 6. AUTOMATIC SHUTDOWN/RESTART

- 6.1 WHEN SMOKE IS DETECTED BY DUCT SMOKE DETECTOR, SD, THE SUPPLY AND RETURN FANS SHALL SHUT "OFF" AND AN ALARM SIGNAL SHALL BE TRANSMITTED TO THE FIRE ALARM SYSTEM. ALL SMOKE DAMPERS IN THE SUPPLY AND RETURN DUCTS SHALL CLOSE.
- 6.2 EXHAUST FANS SERVING AREA OF THE SUPPLY FAN SHALL CONTINUE TO RUN. SUPPLY AND RETURN FANS SHALL RESTART AND SMOKE DAMPERS SHALL OPEN WHEN FIRE ALARM CIRCUIT IS RESET.

## 7. EMERGENCY CONSTANT SPEED OPERATION

- \_7.1 UPON FAILURE OF THE VSMC, THE SUPPLY AND RETURN FANS SHALL BE STARTED/STOPPED MANUALLY AT THE DIGITAL CONTROL PANEL OR THE ECC THROUGH THE BY-PASS STARTER. FANS SHALL THEN BE OPERATED AT CONSTANT SPEED.

DETAIL TITLE / SEQUENCE OF OPERATION FOR VARIABLE AIR VOLUME AIR HANDLING UNIT WITH MINIMUM OUTSIDE AIR

SCALE : NONE

DATE ISSUED: SEPTEMBER 2010


CAD DETAIL NO.: SD230923-05.DWG

Department of  
Veterans Affairs










NOTES:

1. EMERGENCY GENERATOR SHALL BE INTERLOCKED WITH D3. WHEN EMERGENCY GENERATOR IS ENERGIZED D3 SHALL OPEN. WHEN EMERGENCY GENERATOR IS DE-ENERGIZED D3 SHALL CLOSE, PROVIDED ROOM EXHAUST FAN IS OFF.
2. ROOM EXHAUST FAN SHALL BE INTERLOCKED WITH D3 & ROOM THERMOSTAT T1. WHEN ROOM THERMOSTAT RISES ABOVE 85°F [29°C] ROOM EXHAUST FAN SHALL RUN & D3 SHALL OPEN. WHEN ROOM THERMOSTAT DROPS BELOW 80°F [27 C] ROOM EXHAUST FAN SHALL STOP & D3 SHALL CLOSE, PROVIDED EMERGENCY GENERATOR IS DE-ENERGIZED.
3. POWER OPERATED, OPPOSED BLADE, DAMPERS D1 & D2 SHALL BE INTERLOCKED WITH ROOM THERMOSTAT T2 SET AT 60°F [16°C]. ON A RISE IN ROOM TEMPERATURE ABOVE 60°F [16°C] D1 SHALL MODULATE OPEN & D2 SHALL MODULATE CLOSED. ON A DROP IN ROOM TEMPERATURE BELOW 60°F [16°C], D1 SHALL MODULATE CLOSED & D2 SHALL MODULATE OPEN.
4. ELECTRIC UNIT HEATER SHALL BE INTERLOCKED WITH ROOM THERMOSTAT T3 SET AT 45°F [7.2°C]. ON A DROP IN ROOM TEMPERATURE BELOW 43°F [6.1°C] ELECTRIC UNIT HEATER SHALL BE ENERGIZED & ON A RISE IN ROOM TEMPERATURE ABOVE 47°F [8.3°C].



## EMERGENCY GENERATOR ROOM CONTROLS

NTS

DESIGNER'S NOTES:

1. IF THE PROJECT INVOLVES MULTIPLE EMERGENCY GENERATORS, EACH GENERATOR SHALL HAVE A DEDICATED SECTION OF THE OUTSIDE AIR INTAKE LOUVER & DAMPER MOTOR(S) ASSIGNED TO IT. THE DESIGNER SHALL SHOW A SCHEDULE OF THE EMERGENCY GENERATORS & THE SPECIFIC INTERLOCKED LOUVER/DAMPER SECTIONS ON THE FLOOR PLANS.
2. WHEN THE ROOM EXHAUST FAN IS RUNNING ALONE, WITHOUT ANY EMERGENCY GENERATOR, ONLY A DESIGNATED PORTION OF THE OUTSIDE AIR INTAKE LOUVER SHALL OPEN. THE DESIGNER SHALL SHOW THIS SECTION ON THE FLOOR PLANS.




Department of  
Veterans Affairs

DETAIL TITLE / EMERGENCY GENERATOR ROOM CONTROLS

SCALE :NONE

DATE ISSUED :DECEMBER 2008


CADD DETAIL NO. : SD230923-07.DWG



**NOTE:**  
 MAINTAIN UPSTREAM AND DOWN STREAM DISTANCES RECOMMENDED BY METER MANUFACTURERS


**DESIGNER'S NOTE:**  
 MODIFY DETAIL AS REQUIRED TO BE PROJECT SPECIFIC FOR THE TYPE OF METER BEING USED.

# **STEAM METER DETAIL**  
 NTS



CONTROL SYSTEM CONFIGURATION  
 OPTION 1 -  
 NEW BACNET ECC, UPGRADE EXISTING  
 CONTROLS WITH NEW BACNET CONTROLS  
 SYSTEM, INSTALL NEW BACNET  
 COMMUNICATIONS NETWORK.

- NOTES:
1. REPLACE EXISTING ECC WITH NEW BACNET (B-AWS) ENGINEERING CONTROL CENTER.
  2. REPLACE ALL EXISTING CONTROLLERS WITH NEW BACNET CONTROLLERS.
  3. INSTALL NEW BACNET COMMUNICATION NETWORK.
  4. INSTALL MULTIPLE BUILDING CONTROLLERS (B-BC) AS REQUIRED.
  5. INSTALL NEW CONTROLLERS (B-AAC, B-ASC) AS REQUIRED.
  6. PROVIDE NEW PORTABLE OPERATORS TERMINAL.



## BACNET SYSTEM ARCHITECTURE OPTION 1

NTS

DETAIL TITLE / BACNET SYSTEM ARCHITECTURE OPTION 1


Department of  
Veterans Affairs



SCALE : NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-11.DWG



CONTROL SYSTEM CONFIGURATION  
 OPTION 2 –  
 NEW BACNET ECC, INSTALL NEW BACNET CONTROLS ON CURRENT PROJECT, PROVIDE BACNET GATEWAY FOR EXISTING CONTROL SYSTEM. INSTALL NEW BACNET COMMUNICATION NETWORK.

INSTALL NEW GATEWAY FOR COMMUNICATION WITH EXISTING CONTROL SYSTEM

EXISTING CONTROLLER PROTOCOL

- NOTES:
1. REPLACE EXISTING ECC WITH NEW BACNET (B-AWS) ENGINEERING CONTROL CENTER (ECC).
  2. EXISTING CONTROLLERS TO REMAIN.
  3. INSTALL NEW BACNET GATEWAY WITH FULL COMMUNICATION TO EXISTING CONTROLLERS.
  4. INSTALL NEW BACNET COMMUNICATION NETWORK.
  5. INSTALL MULTIPLE BUILDING CONTROLLERS AS REQUIRED.
  6. INSTALL NEW CONTROLLERS (B-AAC/B-ASC) AS REQUIRED.
  7. PROVIDE NEW PORTABLE OPERATORS TERMINAL.

#  
 NTS

## BACNET SYSTEM ARCHITECTURE OPTION 2

DETAIL TITLE / BACNET SYSTEM ARCHITECTURE OPTION 2


Department of  
 Veterans Affairs



SCALE : NONE


DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-12.DWG



CONTROL SYSTEM CONFIGURATION  
 OPTION 3 –  
 NEW BACNET ECC, INSTALL NEW  
 BACNET CONTROLS ON CURRENT  
 PROJECT. INSTALL NEW  
 COMMUNICATIONS NETWORK. EXISTING  
 ECC AND CONTROL TO REMAIN

- NOTES:
1. INSTALL NEW BACNET (B-AWS) ENGINEERING CONTROL CENTER (ECC).
  2. EXISTING ECC, ASSOCIATED COMMUNICATION NETWORK AND CONTROLLERS TO REMAIN.
  3. INSTALL NEW BACNET COMMUNICATION NETWORK.
  4. INSTALL MULTIPLE BUILDING CONTROLLERS (B-BC) AS REQUIRED.
  5. INSTALL NEW CONTROLLERS (B-AAC, B-ASC) AS REQUIRED.
  6. PROVIDE NEW PORTABLE OPERATORS TERMINAL.



## BACNET SYSTEM ARCHITECTURE OPTION 3

NTS

DETAIL TITLE / BACNET SYSTEM ARCHITECTURE OPTION 3


Department of  
Veterans Affairs



SCALE : NONE


DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-13.DWG



CONTROL SYSTEM CONFIGURATION  
 OPTION 4 -  
 EXISTING ECC TO REMAIN, INSTALL NEW BACNET SOFTWARE ON EXISTING ECC. EXISTING CONTROL SYSTEM SOFTWARE TO CO-EXIST ON ECC. INSTALL NEW BACNET CONTROLS ON CURRENT PROJECT, EXISTING CONTROL SYSTEM TO REMAIN, RE-USE EXISTING COMMUNICATION NETWORK.

- NOTES:
1. INSTALL NEW BACNET SOFTWARE ON EXISTING ENGINEERING CONTROL CENTER (ECC.)
  2. REUSE EXISTING COMMUNICATION NETWORK.
  3. EXISTING CONTROLLERS TO REMAIN.
  4. INSTALL MULTIPLE BUILDING CONTROLLERS AS REQUIRED.
  5. INSTALL NEW CONTROLLERS (B-AAC, B-ASC) AS REQUIRED,
  6. PROVIDE NEW PORTABLE OPERATORS TERMINAL.



## BACNET SYSTEM ARCHITECTURE OPTION 4

NTS

DETAIL TITLE / BACNET SYSTEM ARCHITECTURE OPTION 4


Department of  
Veterans Affairs



SCALE : NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-14.DWG



# AIR HANDLING UNIT FOR SURGICAL SUITE (VAV)  
NTS

DETAIL TITLE / AIR HANDLING UNIT FOR SURGICAL SUITE (VAV)

SCALE : NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-15.DWG





# SEQUENCE OF OPERATION FOR AIR HANDLING UNIT FOR SURGICAL SUITE (VAV)

## 1. GENERAL

\_1.1 UNIT IS NORMALLY STARTED AND STOPPED REMOTELY AT THE ECC. THE UNIT WILL NORMALLY OPERATE 24 HOUR/DAY. H-O-A SWITCH SHALL BE KEPT IN THE "AUTO" POSITION. "HAND" AND "OFF" POSITIONS SHALL BE USED ONLY FOR MAINTENANCE. WHEN THE UNIT IS "OFF" D-1, D-3, D-4 AND SHALL BE FULLY CLOSED. WHEN THE UNIT IS "ON" D-4, SD-1 AND SD-2 SHALL BE FULLY OPEN. D-1, D-2 AND D-3 SHALL MODULATE IN ACCORDANCE WITH THE FOLLOWING SEQUENCE:

## 2. TEMPERATURE CONTROL

\_2.1 SUPPLY AIR TEMPERATURE SETPOINT (AS SET BY ECC), SENSED BY SENSOR TT-1, SHALL BE MAINTAINED BY SEQUENCING V-1 AND V-2. HEATING AND COOLING CONTROL VALVES SHALL BE MODULATED VIA PID CONTROL LOOP TO MAINTAIN THE SUPPLY AIR TEMP. VALVES V-1 AND V-2 SHALL NOT BE OPENED SIMULTANEOUSLY.

2.2 WHEN THE OUTSIDE AIR ENTHALPY AS CALCULATED BY TT-2 AND MT-3 IS LOWER THAN THE RETURN AIR ENTHALPY AS CALCULATED BY TT-4 AND MT-1 AND THE OUTSIDE AIR DRY BULB IS LESS THAN THE RETURN/EXHAUST DRY BULB TT-4 THE UNIT ECONOMIZER MODE SHALL BE ENABLED. WHEN THE ECONOMIZER IS ENABLED DAMPERS D-1, D-2, AND D-3 SHALL MODULATE TO MAINTAIN THE DISCHARGE AIR SETPOINT AS SENSED BY THE DISCHARGE AIR SENSOR TT-1.

2.3 WHEN THE OUTSIDE AIR ENTHALPY, OR TEMPERATURE, IS HIGHER THAN THE RETURN AIR ENTHALPY, OR TEMPERATURE, THE ECONOMIZER SHALL BE DISABLED, DAMPERS D-1 AND D-3 SHALL CLOSE, D-2 SHALL OPEN AND D-4 SHALL MODULATE TO MAINTAIN THE MINIMUM OUTSIDE AIR CFM SETPOINT.

## 3. AIR FLOW CONTROL

\_3.1 THE SUPPLY AIR FLOW SHALL BE CONTROLLED BY THE DIGITAL CONTROL PANEL MODULATING THE SUPPLY FAN VARIABLE SPEED MOTOR CONTROLLER TO MAINTAIN THE TOTAL SUPPLY AIR CFM DURING OCCUPIED MODE. RESET SUPPLY AIR CFM AS EACH 2 POSITION AIR TERMINAL UNIT SWITCHES TO UNOCCUPIED MODE.

3.2 THE DIGITAL CONTROL PANEL, USING TOTAL SUPPLY AIR AND RETURN AIR FLOW SIGNALS, SHALL RESET THE RETURN AIR FAN TO MAINTAIN A CONSTANT AIR FLOW DIFFERENCE BETWEEN THE SUPPLY AIR AND THE RETURN AIR EQUAL TO MINIMUM OUTSIDE AIR.

3.3 USING HIGH PRESSURE SENSOR PSH LOCATED AT THE SUPPLY FAN DISCHARGE, SHALL PREVENT THE SUPPLY FAN FROM DEVELOPING OVER 3" [75mm] OF STATIC PRESSURE (FIELD ADJUSTABLE). IF STATIC PRESSURE AT PSH DOES EXCEED 3" [75mm] THE SUPPLY AIR FAN SHALL STOP. PSH SHALL BE HARDWIRED TO THE SUPPLY FAN AND UNIT SHALL BE SHUTDOWN IN HAND, AUTO OR BYPASS MODE. PSH WILL REQUIRE MANUAL RESET AT THE DEVICE.

3.4 USING LOW PRESSURE SENSOR PSL LOCATE AT THE RETURN FAN INLET, SHALL PREVENT THE RETURN FAN FROM DEVELOPING OVER - 3" [75mm] OF NEGATIVE STATICE PRESSURE (FIELD ADJUSTABLE) IF STATIC PRESSURE AT PSL DOES EXCEED - 3" [75mm] THE RETURN AIR FAN SHALL STOP. PSL SHALL BE HARDWIRED TO THE RETURN FAN AND UNIT SHALL BE SHUTDOWN IN HAND, AUTO OR BYPASS MODE. PSL WILL REQUIRE MANUAL RESET.

## 4. HUMIDITY CONTROL

\_4.1 WHEN THE DIGITAL CONTROL PANEL IS NOT CALLING FOR HUMIDITY, SENSED BY RETURN AIR HUMIDITY MT-1, 2-WAY "ON-OFF" CONTROL VALVE V-3 SHALL REMAIN CLOSED. WHEN THE DIGITAL CONTROL PANEL IS CALLING FOR HUMIDITY, V-3 SHALL REMAIN OPEN.

4.2 RETURN AIR HUMIDITY SHALL BE MAINTAINED AT SETPOINT OF 42° F [5.6° C] DEW POINT (ADJ) VIA DIGITAL CONTROL PANEL BY MODULATING CONTROL VALVE V-4 TO MAINTAIN THE DESIRED HUMIDITY. THE DRYBULB TRANSMITTER T-4 AND HUMIDITY TRANSMITTER H-1 IN RETURN AIR SHALL BE USED TO CALCULATE RETURN AIR DEW POINT TEMPERATURE. V-3 SHALL BE CLOSED WHENEVER THE RETURN AIR DEWPOINT IS > 45° F [7°C]. DCP SHALL CLOSE VALVE V-3 WHENEVER THE SUPPLY FAN IS OFF. VALVE V-4 SHALL BE INTERLOCKED WITH A TEMPERATURE SWITCH TO KEEP THE HUMIDIFIER OFF UNTIL CONDENSATE TEMPERATURE APPROACHES STEAM TEMPERATURE.

## 5. FREEZE PROTECTION

\_5.1 IF THE AIR TEMPERATURE AS SENSED BY TT-3 FALLS BELOW 45°F [7°C], AN ALARM SIGNAL SHALL INDICATE AT THE DCP AND ECC. IF THIS TEMPERATURE FALLS BELOW 40°F [4.4°C], AS SENSED BY THE TSL THE SUPPLY AND RETURN FANS SHALL SHUT DOWN AND A CRITICAL ALARM SHALL INDICATE AT THE DIGITAL CONTROL PANEL AND ECC. TSL SHALL BE HARDWIRED TO THE SUPPLY FAN AND RETURN FAN AND BOTH SHALL BE SHUTDOWN IN HAND, AUTO OR BYPASS MODE. TSL WILL REQUIRE MANUAL RESET AT THE DEVICE.

## 6. LOSS OF COOLING PROTECTION

\_6.1 IF THE AIR TEMPERATURE AS SENSED BY TT-1 RAISES ABOVE 65°F [18°C], AN ALARM SIGNAL SHALL INDICATE AT THE DCP AND ECC. IF THIS TEMPERATURE RAISES ABOVE 70°F [21°C], AS SENSED BY TT-1 THE SUPPLY AND RETURN FANS SHALL SHUT DOWN AND A CRITICAL ALARM SHALL INDICATE AT THE DIGITAL CONTROL PANEL AND ECC.

## 7. AUTOMATIC SMOKE SHUTDOWN/RESTART

7.1 WHEN SMOKE IS DETECTED BY DUCT SMOKE DETECTOR, SD, THE SUPPLY AND RETURN FANS SHALL SHUT "OFF" AND AN ALARM SIGNAL SHALL BE TRANSMITTED TO THE FIRE ALARM SYSTEM. ALL SMOKE DAMPERS IN THE SUPPLY AND RETURN DUCTS SHALL CLOSE.

7.2 EXHAUST FANS SERVING AREA OF THE SUPPLY FAN SHALL CONTINUE TO RUN. SUPPLY AND RETURN FANS SHALL RESTART AND SMOKE DAMPERS SHALL OPEN WHEN FIRE ALARM CIRCUIT IS RESET.

## 8. EMERGENCY CONSTANT SPEED OPERATION

\_8.1 UPON FAILURE OF THE VSMC, THE SUPPLY AND RETURN FANS SHALL BE STARTED/STOPPED MANUALLY AT THE DIGITAL CONTROL PANEL OR THE ECC THROUGH THE BY-PASS STARTER. FANS SHALL THEN BE OPERATED AT CONSTANT SPEED.

DETAIL TITLE / SEQUENCE OF OPERATION FOR AIR HANDLING UNIT  
FOR SURGICAL SUITE (VAV)


SCALE : NONE

DATE ISSUED: SEPTEMBER 2010

CAD DETAIL NO.: SD230923-16.DWG

Department of  
Veterans Affairs





LEGEND

V1 AIR FLOW CONTROL VALVE PRESSURE INDEPENDENT TYPE

GENERAL NOTES:

1. MAINTAIN POSITIVE AIR PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL]) BETWEEN THE PE ROOM AND THE ANTEROOM AND THE ANTEROOM AND THE CORRIDOR BY MODULATING VALVE V1. PE ROOMS SHALL HAVE A PERMANENTLY INSTALLED DEVICE AND/OR MECHANISM TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND THE CORRIDOR. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER POSITIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED. (STROBE LITE)
2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE PE ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE THE SUPPLY AIR OUTLET OVER THE PATIENT BED ON THE CEILING WITHOUT CREATING A DRAFT CAUSING PATIENT DISCOMFORT. LOCATE RETURN AIR INLET NEAR THE ROOM DOOR.

TYPICAL AIR BALANCE EXAMPLE:

1. THE PATIENT BEDROOM IS KEPT UNDER POSITIVE PRESSURE BY ENSURING AIR MOVEMENT FROM THE BEDROOM SPACE AND THE ADJOINING CORRIDOR INTO THE ANTE ROOM.
2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE, AS FOLLOWS:

- A - PATIENT BEDROOM 12 ACPH (MINIMUM-ASHRAE STANDARD 170 2008). INCREASE THE SUPPLY AIR VOLUME IF REQUIRED TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODE.  
EXAMPLE: 400 CFM [190 L/S]
- B - ANTE ROOM SUPPLY AIR IS NOT REQUIRED FOR THIS SPACE. EXFILTRATE 100 CFM [47 L/S] OF AIR FROM PATIENT ROOM, THRU ANTE ROOM INTO THE CORRIDOR. EXAMPLE: 100 CFM [28 L/S]
- C - PATIENT TOILET DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28]. EXAMPLE: 60 CFM [28 L/S]
- D - RETURN AIR FROM PATIENT ROOM 400 CFM [189 L/S] (SUPPLY AIR) - 100 CFM [47 L/S] TO ANTE ROOM + 60 CFM [28 L/S] TO TOILET) = 240 CFM [115 L/S] RETURN AIR SETTING OF AFCV V1, IN THE RA DUCT.


#

NTS POSITIVE PRESSURE

DESIGNER'S NOTE:

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.

## AIR SYSTEM FOR PROTECTIVE ENVIRONMENT ROOM (PE) (WITH ANTEROOM)



LEGEND

V1 AIR FLOW CONTROL VALVE PRESSURE INDEPENDENT TYPE

GENERAL NOTES:

1. MAINTAIN POSITIVE AIR PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL]) BETWEEN THE PE ROOM AND THE SPACES THAT ARE NOT THE PE ROOMS INCLUDING THE CORRIDOR BY MODULATING VALVE V1. PE ROOMS SHALL HAVE A PERMANENTLY INSTALLED DEVICE AND/OR MECHANISM TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND THE CORRIDOR. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER POSITIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED. (STROBE LITE)
2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE PE ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE THE SUPPLY AIR OUTLET OVER THE PATIENT BED ON THE CEILING WITHOUT CREATING A DRAFT CAUSING PATIENT DISCOMFORT. LOCATE RETURN AIR INLET NEAR THE ROOM DOOR.

TYPICAL AIR BALANCE EXAMPLE:

1. THE PATIENT BEDROOM IS KEPT UNDER POSITIVE PRESSURE BY ENSURING AIR MOVEMENT FROM THE BEDROOM SPACE AND THE ADJOINING CORRIDOR.
2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE, AS FOLLOWS:

- A - PATIENT BEDROOM 12 ACPH (MINIMUM-ASHRAE STANDARD 170 2008). INCREASE THE SUPPLY AIR VOLUME IF REQUIRED TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODE.  
EXAMPLE: 400 CFM [190 L/S]
- B - PATIENT TOILET DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28 L/S]. EXAMPLE: 60 CFM [28 L/S]
- C - RETURN AIR FROM PATIENT ROOM 400 CFM [189 L/S] (SUPPLY AIR) - 100 CFM [47 L/S] TO CORRIDOR + 60 CFM [28 L/S] TO TOILET) = 240 CFM [115 L/S] SETTING OF AFCV V1, IN THE RA DUCT.


#

NTS POSITIVE PRESSURE

DESIGNER'S NOTE:

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.

## AIR SYSTEM FOR PROTECTIVE ENVIRONMENT ROOM (PE) (WITHOUT ANTEROOM)



**LEGEND**

V1 AND V2 AIR FLOW CONTROL VALVES PRESSURE INDEPENDENT TYPE

**GENERAL NOTES:**

1. ANTEROOM SHALL BE MAINTAINED AT A NEGATIVE PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL] WITH RESPECT TO BOTH AII/PE ROOM AND THE CORRIDOR OR ANY ADJOINING SPACE BY MODULATING VALVE V2. VALVE V1 IS USED TO MAINTAIN A POSITIVE PRESSURE BETWEEN THE PATIENT ROOM AND THE ANTE ROOM. COMBO ROOMS SHALL HAVE PERMANENTLY INSTALLED DEVICES AND/OR MECHANISMS TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND ANTE ROOM AND THE CORRIDOR AND THE ANTE ROOM. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER POSITIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED IN THE PATIENT ROOM WITH RESPECT TO THE ANTE ROOM (STROBE LITE). A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER NEGATIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED IN THE ANTE ROOM WITH RESPECT TO THE CORRIDOR (STROBE LITE).

2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE AII/PE ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE THE SUPPLY AIR OUTLET OVER THE PATIENT BED ON THE CEILING WITHOUT CREATING A DRAFT CAUSING PATIENT DISCOMFORT. LOCATE EXHAUST AIR INLET NEAR THE PATIENT ROOM DOOR.

**TYPICAL AIR BALANCE EXAMPLE:**

1. THE PATIENT BEDROOM IS KEPT UNDER POSITIVE PRESSURE BY ENSURING AIR MOVEMENT FROM THE BEDROOM SPACE TO THE ANTE ROOM BY MODULATING VALVE V1. THE ANTE ROOM IS KEPT AT NEGATIVE PRESSURE WITH RESPECT TO THE CORRIDOR BY MODULATING VALVE V2.

2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE AS FOLLOWS:

A – PATIENT BEDROOM

MINIMUM 12 ACPH SUPPLY AIR (ASHRAE STANDARD 170 2008). INCREASE SUPPLY AIR VOLUME, IF REQUIRED, TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODES. EXAMPLE: 400 CFM [190 L/S]

B – ANTE ROOM

SUPPLY AIR IS NOT REQUIRED FOR THIS SPACE. EX-FILTRATE PATIENT ROOM AIR AND CORRIDOR AIR TO EXHAUST MINIMUM 10 ACPH (ASHRAE STANDARD 170) AS MEASURED AND CONTROLLED BY VALVE V-2. FOR THIS EXAMPLE INFILTRATE 100 CFM [47 L/S] FROM CORRIDOR INTO THE ANTEROOM + 60 CFM [28 L/S] FROM THE AII/PE ROOM. THIS WILL ENSURE THE ANTE ROOM IS NEGATIVE WITH RESPECT TO THE AII/PE ROOM AND WITH RESPECT TO THE CORRIDOR.

C – PATIENT TOILET

DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28 L/S]. EXAMPLE: 60 CFM [28 L/S]

3. THE DEDICATED EXHAUST AIR SYSTEM SHALL BE BALANCED AS FOLLOWS:

A – PATIENT BEDROOM 400 CFM [190 L/S](SUPPLY) – 60 CFM [28 L/S](TOILET) – 40 CFM [19 L/S] (ANTE ROOM). 300 CFM [140 L/S] AII/PE ROOM EXHAUST. 100 CFM [47 L/S] INFILTRATED FROM CORRIDOR INTO ANTE ROOM + 40 CFM [19 L/S] EXFILTRATE FROM AII/PE ROOM INTO ANTE ROOM, 140 CFM [65 L/S] EXHAUST, TOTAL EXHAUST 500 CFM [240 L/S]

4. COORDINATE DOORS UNDER CUTS FOR DOOR BETWEEN ANTE ROOM AND PATIENT (1") [2.54 CM], DOOR TO CORRIDOR.

## AIR SYSTEM FOR COMBINATION AIRBORNE INFECTION ISOLATION (AII)/PROTECTIVE ENVIRONMENT (PE) ROOM WITH NEGATIVE ANTEROOM


#

NTS

NEGATIVE PRESSURE

**DESIGNER'S NOTE:**

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.



LEGEND

V1 AIR FLOW CONTROL VALVE PRESSURE INDEPENDENT TYPE

GENERAL NOTES:

1. ANTEROOM SHALL BE MAINTAINED AT A POSITIVE PRESSURE (0.01 INCH WATER COLUMN [2.5 PASCAL]) WITH RESPECT TO BOTH AII/PE ROOM AND THE CORRIDOR OR ANY ADJOINING SPACE BY MODULATING VALVE V1. COMBO ROOMS SHALL HAVE PERMANENTLY INSTALLED DEVICES AND/OR MECHANISMS TO CONSTANTLY MONITOR THE DIFFERENTIAL AIR PRESSURE BETWEEN THE PATIENT ROOM AND ANTE ROOM AND THE CORRIDOR AND ANTE ROOM. A LOCAL VISUAL MEANS SHALL BE PROVIDED TO INDICATE WHENEVER POSITIVE DIFFERENTIAL PRESSURE IS NOT MAINTAINED WITH RESPECT TO ANTE ROOM AND EITHER THE AII/PE ROOM OR THE CORRIDOR. (STOBE LITE)
2. MAINTAIN THE ATTACHED TOILET, IF ANY, AT NEGATIVE AIR PRESSURE WITH RESPECT TO THE PE ROOM. HOWEVER, THE DESIGN NEED NOT INCLUDE A PRESSURE DIFFERENTIAL SENSOR FOR VERIFICATION.
3. LOCATE THE SUPPLY AIR OUTLET OVER THE PATIENT BED ON THE CEILING WITHOUT CREATING A DRAFT CAUSING PATIENT DISCOMFORT. LOCATE EXHAUST AIR INLET NEAR THE PATIENT ROOM DOOR.

TYPICAL AIR BALANCE EXAMPLE:

1. THE PATIENT BEDROOM IS KEPT UNDER POSITIVE PRESSURE WITH RESPECT TO THE ADJOINING CORRIDOR BY MODULATING VALVE V1.
2. THE SUPPLY AIR SYSTEM SHALL CONSIST OF THE CONSTANT VOLUME AIR DELIVERY FROM A DEDICATED AIR TERMINAL UNIT WITH REHEAT COIL TO THE ISOLATION SUITE AS FOLLOWS:

A – PATIENT BEDROOM

MINIMUM 12 ACPH SUPPLY AIR (ASHRAE STANDARD 170 2008). INCREASE SUPPLY AIR VOLUME; IF REQUIRED, TO MEET THE INSIDE DESIGN CONDITIONS IN COOLING AND/OR HEATING MODES. EXAMPLE: 400 CFM [190 L/S]

B – ANTE ROOM

MINIMUM 10 ACPH (ASHRAE STANDARD 170 2008) TO BE EX-FILTRATED TO THE CORRIDOR AND INTO AII/PE ROOM AS FOLLOWS: SUPPLY ANTE ROOM AT THE RATE OF 140 CFM [66 L/S] WITH 40 CFM [19 L/S] ENTERING THE AII/PE ROOM AND 100 CFM [47 L/S] EX-FILTRATED INTO THE CORRIDOR. EXAMPLE: 140 CFM [66 L/S] TOTAL SUPPLY AIR

C – PATIENT TOILET

DO NOT SUPPLY AIR INTO THE TOILET. DRAW MAKE-UP AIR FROM THE PATIENT'S BEDROOM AND EXHAUST AT THE RATE OF 10 ACPH OR 60 CFM [28 L/S]. EXAMPLE: 60 CFM [28 L/S]

3. THE DEDICATED EXHAUST AIR SYSTEM SHALL BE BALANCED AS FOLLOWS:

A – PATIENT BEDROOM

400 CFM [190 L/S] (SUPPLY) – 60 CFM [28 L/S] (TOILET) + 40 CFM [19 L/S] INFILTRATED FROM ANTE ROOM (ANTE ROOM) 380 CFM [180 L/S] EXHAUSTED FROM AII/PE ROOM. 100 CFM [47 L/S] IS EXFILTRATED TO CORRIDOR FROM ANTE ROOM. TOTAL EXHAUST 440 CFM [210 L/S]

4. COORDINATE DOORS UNDER CUTS FOR DOOR BETWEEN ANTE ROOM AND PATIENT (1") [2.54 CM], DOOR TO CORRIDOR.

## AIR SYSTEM FOR COMBINATION AIRBORNE

### INFECTION ISOLATION (AII)/PROTECTIVE

### ENVIRONMENT (PE) ROOM WITH POSITIVE ANTEROOM




#

NTS POSITIVE PRESSURE

DESIGNER'S NOTE:

1. ENSURE FINAL DESIGN REFLECTS PROJECT SPECIFIC REQUIREMENTS AND MEETS ASHRAE 170, LATEST EDITION WITH **ALL** ADDENDUMS.


NOTE: THIS DETAIL SHOWS BASIC REQUIREMENTS ONLY AND IS NOT INTENDED FOR USE ON PROJECT DRAWINGS. THE PROJECT ENGINEER MUST PROVIDE A COMPLETE DESIGN WHICH CONFORMS TO PROJECT REQUIREMENTS.



REINFORCED CONCRETE BALLAST PAD  
DESIGN FOR BUOYANCY OF EMPTY  
TANK WITH CREDIT FOR BACKFILL

LADDER  
STEEL OR ALUMINUM 2 1/2"  
[64mm] WIDE STRINGERS  
3/4" [19mm] DIA. RUNGS  
ANCHOR AT BOTTOM GUIDE AT  
TOP

# UNDERGROUND FUEL OIL STORAGE TANK



NTS



DETAIL TITLE / UNDERGROUND FUEL OIL STORAGE TANK

SCALE : NONE

DATE ISSUED : DECEMBER 2008


CADD DETAIL NO. SD231000-01.DWG





STEAM LINE DRIP POCKET


NOTE:  
 DRIP POCKET PIPE SIZE SAME AS STEAM  
 MAIN UNLESS OTHERWISE NOTED.



#


NTS

# STEAM LINE DRIP POCKET AND STEAM TRAP ASSEMBLY



**NOTES:**

1. UNLESS OTHERWISE SHOWN ON THE DRAWINGS, SIZE THE VENT PIPE SO THAT STEAM IS NOT BLOWN OUT AT THE VENT PIPE ENTRANCE. UTILIZE THE CALCULATION METHOD CONTAINED IN ANSI B31.1. POWER PIPING CODE, APPENDIX II.
2. VENT PIPE SHALL TERMINATE 1829mm [6'] MIN. ABOVE FINISHED ROOF.
3. DISCHARGE OF DRAIN SHALL BE DIRECTED AWAY FROM PLATFORMS OR OTHER AREAS WHICH PERSONNEL MAY OCCUPY.
4. NO OTHER DRAIN SHALL BE CONNECTED TO THE DRIP PAN ELBOW DRAIN PIPE.



# STEAM SAFETY VALVE

NTS



U.S. Department of Veterans Affairs

DETAIL TITLE / STEAM SAFETY VALVE


SCALE: NONE

DATE ISSUED: NOVEMBER 1, 2020


SD232111-02 DWG



- DESIGNER NOTES:
1. PROJECT DESIGN AND FLOW DIAGRAM SHALL BE IN CONFORMANCE WITH SPECIFICATIONS.
  2. SHOW VALVES THREADED OR FLANGED TO SUIT THE PROJECT.
  3. ENGINEERING NOTES FOR MPS DISTRIBUTION PRIV ARE TYP. FOR ALL PRIVS.
  4. PRIMARY ELEMENT LOCATIONS SHALL CONFORM TO REQUIREMENTS OF INSTRUMENT MANUFACTURER.
  5. DELETE "DESIGNER NOTES" FROM PROJECT DRAWINGS WHEN COMPLETED.
  6. SHOW ALL PIPE SIZES.
  7. DO NOT SCHEDULE BOILER SAFETY VALVES.
  8. DO NOT SIZE VENT PIPES FROM BOILER SAFETY VALVES. CONTRACTOR MUST DO THIS BASED ON VALVES FURNISHED.




# STANDARD STEAM BOILER PLANT PIPING DIAGRAM  
N/S




- NOTES:
1. DEAREATOR OVERFLOW ONLY PERMITTED TO GO TO CONDENSATE TANK IF THE CONDENSATE TANK IS A ASME CODE TANK WITH SAME MAWP AS THE DEAREATOR.
  2. FOR COMPLETE PIPING SEE REFERENCED DETAILS.

# BASIC FLOW DIAGRAM - CONDENSATE AND BOILER FEEDWATER  
NTS



DESIGNER'S NOTE:  
SEE SD232111-04 BASIC FLOW DIAGRAM - CONDENSATE AND BOILER FEEDWATER FOR COMPLETE SYSTEM.



# CONDENSATE STORAGE AND TRANSFER FLOW DIAGRAM  
NTS



DETAIL TITLE: CONDENSATE STORAGE AND TRANSFER FLOW DIAGRAM




SCALE : NONE

DATE ISSUED: 11/01/2017


CAD DETAIL NO.: SD232111-05.DWG



WATER LEVEL CONTROL/ALARM POINTS



WATER LEVEL CONTROL SCHEMATIC



OVERFLOW CONTROL SCHEMATIC


DESIGNER'S NOTE:  
 1. SEE SD232111-04 BASIC FLOW DIAGRAM - CONDENSATE AND BOILER FEEDWATER FOR COMPLETE SYSTEM.  
 2. DELETE DESIGNER'S NOTE WHEN COMPLETED.

# FEEDWATER DEAERATOR FLOW DIAGRAM  
 NTS

DETAIL TITLE / FEEDWATER DEAERATOR FLOW DIAGRAM



SCALE: NONE  
 DATE ISSUED: NOVEMBER 1, 2020  
 SD232111-06.DWG








DESIGNER'S NOTE:  
SEE SD232111-04 BASIC FLOW DIAGRAM -  
CONDENSATE AND BOILER FEEDWATER FOR  
COMPLETE SYSTEM.

NOTE:  
CAPACITY OF EACH PUMP APPROX. 125% OF ONE BOILER.

#  
NTS  
**BOILER FEEDWATER PUMPS FLOW DIAGRAM**

THIS RELIEF VALVE IS HOT WATER UNDER PRESSURE AND SHOULD BE VENTED DOWN TO THE FLOOR TWO INCHES ABOVE FLOOR DRAIN OR IN A TRENCH DRAIN IS PREFERRED. LIKE A SAFETY VALVE ON A HOT WATER HEATER.



BOILER WATER LEVEL CONTROL SCHEMATIC  
(SEE SPECS FOR TYPE OF SYSTEM)

# # BOILER FLOW DIAGRAM

NTS


DETAIL TITLE / BOILER FLOW DIAGRAM



SCALE: NONE

DATE ISSUED: NOVEMBER 1, 2020

SD232111-08.DWG



A	SIZE, TRAP DISCHARGE LINE	15mm [1/2"]	20mm [3/4"]
B	SIZE, 45° WELDING NIPPLE	25mm [1"]	32mm [1-1/4"]
C	LENGTH OF EXPANDED MAIN AHEAD OF TRAP DISCHARGE PIPE	175mm [7"]	175mm [7"]
D	LENGTH OF PERFORATED PIPE	415mm [16-1/2"]	415mm [16-1/2"]
E	LENGTH OF EXPANDED MAIN FOLLOWING PERFORATED PIPE	50mm [2"]	50mm [2"]

RETURN MAIN SIZE	UP TO 40mm [1-1/2"]	50mm [2"]	75mm [3"] & OVER
EXPANDED RETURN MAIN SIZE		65mm [2-1/2"]	SAME SIZE


**NOTES:**

1. 15mm [1/2"] PERFORATED TUBE SHALL HAVE 40 - 16mm [1/8"] DIAMETER HOLES SPACED 40mm [1-1/2"] O.C. IN 4 ROWS.
2. 20mm [3/4"] PERFORATED TUBE SHALL HAVE 78 - 6mm [1/8"] DIAMETER HOLES SPACED 40mm [1-1/2"] O.C. IN 6 ROWS.
3. HOLES IN TUBE SHALL BE SPACED EQUALLY AROUND PERIMETER.

**DESIGNER'S NOTE:**

THIS DETAIL SHALL ONLY BE USED FOR LIMITED SITUATIONS WHERE THE DESIGNER CONDUCTS A FULL ANALYSIS OF THE SYSTEM AND ITS IMPACTS, TO ENSURE THAT CONDENSATE DOES NOT FLASH AND CREATE A WATER HAMMER. REFERENCE THE STEAM DESIGN MANUAL VOLUME 3.

# HIGH PRESSURE STEAM TRAP DISCHARGE INTO PUMPED CONDENSATE RETURN LINE



NTS




Department of  
Veterans Affairs

DETAIL TITLE: HIGH PRESSURE STEAM TRAP DISCHARGE  
INTO PUMPED CONDENSATE RETURN LINE

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD232111-09.DWG



NOTE:  
 MAINTAIN UPSTREAM AND DOWNSTREAM DISTANCES RECOMMENDED BY METER MANUFACTURERS.

DESIGNER'S NOTE:  
 MODIFY DETAIL AS REQUIRED TO BE PROJECT SPECIFIC FOR THE TYPE OF METER BEING USED.

# WATER FLOW MEASURING STATION (WITH BTU METER)

#

NTS



Department of  
 Veterans Affairs


DETAIL TITLE: WATER FLOW MEASURING STATION

SCALE :NONE


DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD232113-01.DWG






GREATER THAN 50mm [2"] DIA. PIPE




50mm [2"] DIA. & SMALLER

HORIZONTAL




GREATER THAN 50mm [2"] DIA. PIPE



50mm [2"] DIA. & SMALLER

VERTICAL

NOTE:  
 PROVIDE THE APPROPRIATE WELL DEPTH TO HAVE THE NECESSARY  
 INSULATION STAND-OFF DISTANCE.



# INSTALLATION OF THERMOMETER WELLS

NTS




Department of  
 Veterans Affairs

DETAIL TITLE: INSTALLATION OF THERMOMETER WELLS

SCALE :NONE

DATE ISSUED :11/01/2017

CADD DETAIL NO. : SD232113-02.DWG



# TUBING, PIPING, AND CONDUITS PASSING THROUGH PRE-FAB INSULATED WALL PANELS

#

NTS




Department of  
Veterans Affairs

DETAIL TITLE: TUBING, PIPING, AND CONDUITS PASSING THROUGH PRE-FAB INSULATED WALL PANELS

SCALE :NONE

DATE ISSUED :11/01/2017

CADD DETAIL NO. : SD232113-03.DWG



**NOTES:**

1. SEE EXPANSION TANK SYSTEM SCHEDULE FOR COMPONENT SIZES.
2. RELIEF VALVE FOR CHILLED WATER SYSTEM IS SHOWN. OMIT WHEN RELIEF VALVE IS SHOWN ON HEAT EXCHANGER DETAIL & SYSTEM IS USED ONLY FOR HOT WATER HEATING.
3. PROVIDE STRAINER IN AIR SEPARATOR WHEN INDICATED IN EXPANSION TANK SCHEDULE.
4. FOR HOT WATER SYSTEMS 50mm [2"] AND SMALLER AND CHILLED WATER SYSTEMS USE IN-LINE AIR PURGER IN LIEU OF AIR SEPARATOR.
5. SET PRESSURE REDUCING VALVE SO PRESSURE AT HIGHEST POINT IN SYSTEM HAS A MINIMUM OF 28kPa. [4 PSIG]

**DESIGNER'S NOTE:**  
 VALVES SHALL BE INDICATED ON EITHER SIDE OF AIR SEPARATOR AS REQUIRED BY CLOSENESS OF VALVES SERVING ADJACENT EQUIPMENT. WHERE CHARGING OF TANK IS PROPOSED PROVIDE NECESSARY TAPPINGS. PROVIDE AND SHOW A LOW WATER ALARM ON CHARGED SYSTEMS TO INDICATE NO WATER IN TANK.

# HORIZONTAL EXPANSION TANK - PIPING CONNECTIONS

#

NTS




Department of  
Veterans Affairs

DETAIL TITLE: FLOOR MOUNTED EXPANSION TANK -  
PIPING CONNECTIONS

SCALE :NONE

DATE ISSUED: 11/01/2017

CAD DETAIL NO.: SD232113-05.DWG



**NOTES:**

1. SEE EXPANSION TANK SYSTEM SCHEDULE FOR COMPONENT SIZES.
2. FOR HOT WATER SYSTEMS 50mm [2"] AND SMALLER AND CHILLED WATER SYSTEMS USE IN-LINE AIR PURGER IN LIEU OF AIR SEPARATOR.
3. SET PRESSURE REDUCING VALVE SO PRESSURE AT HIGHEST POINT IN SYSTEM HAS A MINIMUM OF 28kPa [4 PSIG].
4. PROVIDE STRAINER IN AIR SEPARATOR IF INDICATED IN EXPANSION TANK SCHEDULE.
5. RELIEF VALVE FOR CHILLED WATER SYSTEM IS SHOWN. OMIT WHEN RELIEF VALVE IS SHOWN ON HEAT EXCHANGER DETAIL AND SYSTEM IS USED ONLY FOR HOT WATER HEATING.


**DESIGNER'S NOTE:**

GATE VALVES SHALL BE INDICATED ON EITHER SIDE OF AIR SEPARATOR AS REQUIRED BY CLOSENESS OF VALVES SERVING ADJACENT EQUIPMENT. WHERE CHARGING OF TANK IS PROPOSED PROVIDE NECESSARY TAPPINGS. PROVIDE AND SHOW A LOW WATER ALARM ON CHARGED SYSTEMS TO INDICATE NO WATER IN TANK.

#

NTS

# FLOOR MOUNTED EXPANSION TANK - PIPING CONNECTIONS



**NOTES:**

1. PROVIDE LOW WATER LEVEL ALARM. PROVIDE A LOW WATER LEVEL AT ECC. RELIEF VALVE DRAIN SHALL RETURN TO TANK AS SHOWN ON THIS DETAIL.
2. SET REGULATING VALVE TO MAINTAIN MAKE-UP PRESSURE AT 15 PSIG [103 kPa] ABOVE HIGHEST SYSTEM PRV SETTING.
3. MAKE-UP PIPING SYSTEM DOES NOT REQUIRE INSULATION.
4. OPERATE PUMP MANUALLY AS REQUIRED TO FILL.

## INDIRECT GLYCOL MAKE-UP SYSTEM (PIPING AND CONTROLS)

#

NTS

**DESIGNER'S NOTE:**

PLUMBING DRAWINGS SHOULD INCLUDE DOMESTIC COLD-WATER HOSE BIB NEAR THE GLYCOL-WATER MAKE-UP SYSTEM. FOR SMALL SYSTEMS (50 GAL [200 L] OR LESS) A POT FEEDER, AT THE HIGH POINT IN THE PIPING, MAY BE USED FOR MAKE-UP IN LIEU OF THE PUMPED MAKE-UP.




Department of  
Veterans Affairs

DETAIL TITLE / INDIRECT GLYCOL MAKE-UP SYSTEM  
(PIPING AND CONTROLS)

SCALE :NONE

DATE ISSUED :MARCH 2010

CADD DETAIL NO. : SD232113-06.DWG




## TYPICAL CHILLED AND HOT WATER PIPING DRAIN VALVE CONNECTIONS

**NOTES:**

1. DRAIN ALL LOW POINTS AS INDICATED ABOVE.
2. WHERE SCALE POCKETS ARE SHOWN ON PIPE RISER DIAGRAMS AND/OR PLANS LOCATE DRAIN AT BOTTOM OF SCALE POCKET.

**DESIGNER'S NOTE:**

SHOW SCALE POCKETS ON MAJOR CIRCULATING WATER PIPING RISER DIAGRAMS AND/OR PLANS.




## TYPICAL MANUAL AIR VENT

**NOTES:**

1. VENT ALL HIGH POINTS INDICATED ABOVE.
2. IF AUTOMATIC AIR VENTS ARE USED, PIPE DISCHARGE TO DRAIN.

# DRAIN VALVE AND AIR VENT CONNECTIONS (HYDRONIC SYSTEMS)



NTS



Department of  
Veterans Affairs

DETAIL TITLE / DRAIN VALVE AND AIR VENT CONNECTIONS  
(HYDRONIC SYSTEMS)

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD232113-07.DWG


DRAIN LINE SHALL BE AT LEAST THE SAME  
 SIZE AS THE NIPPLE ON THE DRAIN PAN  
 PIPING SHALL BE RIGID COPPER TYPE L OR  
 TYPE M UNLESS NOTE BELOW IS MET

PITCH DOWN  
 TOWARD DRAIN

CLEAN OUT

1"  
 [25mm]


FLOOR SINK



NOTE: 1. CPVC PIPE MAY BE USED ONLY IF APPROVED BY  
 LOCAL VA AND IS INDOORS AND DOES NOT PASS THROUGH  
 RATED BARRIERS.  
 2. DIELECTRIC FITTING TO BE USED WHEN TWO DISSIMILAR  
 METALS ARE TO BE CONNECTED.

UNIT TYPE	A	B
DRAW THRU	2" [50mm] PLUS X	X
BLOW THRU	1" [25mm] MINIMUM	2X

WHERE X = STATIC PRESSURE IN PAN



## AIR HANDLING UNIT DRAIN TRAP DETAIL

NTS




Department of  
 Veterans Affairs

DETAIL TITLE / AIR HANDLING UNIT DRAIN TRAP DETAIL

SCALE :NONE


DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD232113-08.DWG



EXPANSION LOOP		
LOOP NO.	W	H
100-ELI	---	---
---	---	---

## EXPANSION LOOP DETAIL



# EXPANSION LOOP DETAIL

NTS



Department of  
Veterans Affairs

DETAIL TITLE / EXPANSION LOOP DETAIL

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD232113-09.DWG





**SEQUENCE OF OPERATION:**

1. STEAM CONTROL VALVE SHALL MODULATE TO MAINTAIN THE LEAVING HOT WATER TEMPERATURE AT SET POINT.
2. THE LEAVING HOT WATER TEMPERATURE SHALL BE RESET INVERSELY WITH THE OUTDOOR TEMPERATURE AS SCHEDULED.
3. THE LEAD AND LAG PUMPS AND HEAT EXCHANGERS SHALL BE SEQUENTIAL BY THE OPERATOR CONTROLS AT THE PRE-DETERMINED INTERVAL (USUALLY 7 DAYS). IN THE EVENT THE PUMP FAILS TO START WITHIN 30 SECONDS, AN ALARM SHALL BE INITIATED AND THE SECOND PUMP SHALL START AUTOMATICALLY.


**VALVE SEQUENCE:**

1. SUGGESTED VALVE SEQUENCE. DELETE THIS SEQUENCE FROM THIS DETAIL IF SEQUENCE IS SHOWN ON CONTROLS DRAWINGS OR SPECS.
2. V-1 (1/3) MODULATES TO MAINTAIN HW TEMPERATURE AT SETPOINT. WHEN V-1 HAS REACHED FULLY OPEN POSITIONS, V-2 (2/3) STARTS TO MODULATE OPEN.
3. IF HX-2, V-3 AND V-4 ARE NOT REDUNDANT BACKUP, THEN THE STAGING ABOVE CONTINUES AS FOLLOWS: PROVIDE, ADDITIONAL MOTORIZED ISOLATION VALVES AT THE THE HWS AND HWR FOR EACH HX'S. WHEN V-2 HAS REACHED FULLY OPEN POSITION, THE ISOLATION VALVES AT HX-2 HWS HWS AND HWR LINES FULLY OPEN, AFTER WHICH V-3 (1/3) STARTS TO MODULATE OPEN. WHEN V-3 HAS REACHED FULLY OPEN POSITION. V-4 (2/3) STARTS TO MODULATE OPEN.



**DUAL HEAT EXCHANGER CONTROLS (HEATING SYSTEM)**

NTS




DETAIL TITLE: DUAL HEAT EXCHANGER CONTROLS (HEATING SYSTEM)

SCALE :NONE

DATE ISSUED :11/01/2017

CADD DETAIL NO. : SD232113-10.DWG



SEE SCHEDULES FOR RELIEF VALVE SETTING

RUN DRAIN LINE FROM RELIEF VALVE TO NEAREST FLOOR DRAIN. (TYP.)

DDC PRESSURE SENSORS (TYP.)

IF INSTALLED LOWER THAN MAIN HPS LINE, PROVIDE ANOTHER SCALE POCKET/TRAP HERE.

DDC TEMPERATURE SENSORS (TYP.)

IF THE SECOND HEAT EXCHANGER IS NOT A REDUNDANT 100% BACK UP UNIT, THEN PROVIDE A MOTORIZED ISOLATION VALVE HERE.


IF THE SECOND HEAT EXCHANGER IS NOT A REDUNDANT 100% BACK UP UNIT, THEN PROVIDE A MOTORIZED ISOLATION VALVE HERE.

**NOTES:**


1. THE ABOVE DETAIL SHOWS REQUIRED PIPING FOR TWO HEAT EXCHANGERS IN PARALLEL. INDICATE IF 100% REDUNDANT OR NOT.
2. PROVIDE SADDLE SUPPORTS AND LEGS OR HANGERS FOR HEAT EXCHANGER. MOUNTING HEIGHT SHALL BE ADJUSTED TO FACILITATE GRAVITY RETURN OF STEAM CONDENSATE.
3. MAKE THE BYPASS THE SAME SIZE AS THE CONNECTIONS TO THE CONTROL VALVES.
4. CONTROL VALVES SHALL BE IN A 3 AND 3 SIZE ARRANGEMENT.

# # HEAT EXCHANGER - STEAM TO HOT WATER

NTS



## TERMINAL UNIT WATER COILS - PIPING CONNECTIONS



NTS

### DESIGNER'S NOTE:

1. THIS DETAIL IS APPLICABLE TO: 2-PIPE FAN COIL UNITS (CHILLED OR HOT WATER)
  - o VAV/CV AIR TERMINAL UNITS ( REHEAT COIL)
  - o DUCT-MOUNTED REHEAT COIL
  - o CABINET UNIT HEATERS




Department of  
Veterans Affairs

DETAIL TITLE / TERMINAL UNIT WATER COILS -  
PIPING CONNECTIONS

SCALE :NONE

DATE ISSUED: DECEMBER 2008


CAD DETAIL NO.: SD232113-12.DWG



**NOTE:**

1. PROVIDE IN CHILLED WATER MAIN AND IN CONDENSER WATER MAIN.
2. LOCATE PILOT TUBE TAPS 20 PIPE DIAMETERS DOWNSTREAM AND 10 PIPE DIAMETERS UPSTREAM FROM THE NEAREST PIPE FITTING.

EITHER TOP OR SIDE LOCATION. BOTH ARE NOT REQUIRED AT SAME LOCATION.



## PITOT TEST CONNECTIONS

NTS

**DESIGNER'S NOTE:**

SHOW LOCATION OF PILOT TEST CONNECTIONS ON FLOOR PLANS FOR CONDENSER WATER PIPING TO COOLING TOWER. THIS IS REQUIRED FOR FLOW MEASUREMENT BY ASME COOLING TOWERS TEST CODE.



Department of  
Veterans Affairs


DETAIL TITLE / PITOT TEST CONNECTIONS

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.:

SD232113-13.DWG



**NOTES:**

1. PROVIDE LOW WATER LEVEL ALARM. PROVIDE A LOW WATER LEVEL AT ECC. RELIEF VALVE DRAIN SHALL RETURN TO A 55 GALLON DRUM.
2. SET REGULATING VALVE TO MAINTAIN MAKE-UP PRESSURE AT 15 PSIG [103 kPa] ABOVE HIGHEST SYSTEM PRV SETTING.
3. MAKE-UP PIPING SYSTEM DOES NOT REQUIRE INSULATION.
4. OPERATE PUMP MANUALLY AS REQUIRED TO FILL.

## MOBILE INDIRECT GLYCOL MAKE-UP SYSTEM (PIPING AND CONTROLS)

#

NTS

**DESIGNER'S NOTE:**

PLUMBING DRAWINGS SHOULD INCLUDE DOMESTIC COLD-WATER HOSE BIB NEAR THE GLYCOL-WATER MAKE-UP SYSTEM. FOR SMALL SYSTEMS (50 GAL [200 L] OR LESS) A POT FEEDER, AT THE HIGH POINT IN THE PIPING, MAY BE USED FOR MAKE-UP IN LIEU OF THE PUMPED MAKE-UP.



Department of  
Veterans Affairs


DETAIL TITLE / MOBILE INDIRECT GLYCOL MAKE-UP SYSTEM  
(PIPING AND CONTROLS)

SCALE :NONE

DATE ISSUED :MARCH 2010


CADD DETAIL NO. : SD232113-14.DWG

PIPE HANGERS – PROVIDE DOUBLE DEFLECTION NEOPRENE (TYPE HN) FOR FIRST TWO ON EACH SIDE OF PUMP (SEE NOTE NO. 1)



NOTES:

1. SUPPORT PUMP FROM PIPING ONLY. DO NOT SUPPORT PUMP FROM MOTOR.



## IN-LINE PUMPS – CONNECTIONS

NTS

DESIGNER'S NOTE:

1. CHECK VALVE IS OPTIONAL FOR SINGLE PUMP, EXCEPT FOR COOLING TOWER PUMP.
2. ELIMINATE BALANCING DEVICE WHEN PUMP CONTROLLED BY VARIABLE SPEED DRIVE.



Department of  
Veterans Affairs


DETAIL TITLE / IN-LINE PUMPS – CONNECTIONS

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD232123-01.DWG


FIRST 3 HANGERS FOR EACH PIPE AND BRANCH SHALL BE SPRING & NEOPRENE TYPE. TYPE "H" FOR 4" [100mm] DIA. PIPE & SMALLER. TYPE "H-P" FOR 5" [125mm] DIA. PIPE & LARGER.



**NOTES:**

SEE SPECIFICATION SECTION "PUMPS" FOR Y STRAINER OPTION

# SINGLE SUCTION FLOOR-MOUNTED PUMPS - CONNECTIONS WITH FLEXIBLE CONNECTORS



NTS

**DESIGNER'S NOTE:**

CHECK VALVE IS OPTIONAL FOR SINGLE PUMP, EXCEPT FOR COOLING TOWER PUMP.



Department of  
Veterans Affairs


DETAIL TITLE / SINGLE SUCTION FLOOR-MOUNTED PUMPS -  
CONNECTIONS WITH FLEXIBLE CONNECTORS

SCALE :NONE

DATE ISSUED :DECEMBER 2008

CADD DETAIL NO. : SD232123-02.DWG

FIRST 3 HANGERS FOR EACH PIPE AND BRANCH SHALL BE SPRING & NEOPRENE TYPE. TYPE "H" FOR 4" [100mm] DIA. PIPE & SMALLER. TYPE "H-P" FOR 5" [125mm] DIA. PIPE & LARGER.



NOTES:  
SEE SPECIFICATION SECTION "PUMPS" FOR Y STRAINER OPTION

# SINGLE SUCTION FLOOR-MOUNTED PUMPS - CONNECTIONS WITH MECHANICAL COUPLINGS

#

NTS

DESIGNER'S NOTE:

1. CHECK VALVE IS OPTIONAL FOR SINGLE PUMP, EXCEPT FOR COOLING TOWER PUMP. USE THIS DETAIL ONLY FOR PUMPS IN A MECHANICAL BUILDING WHERE POSSIBLE VIBRATION WILL NOT BE OBJECTIONABLE AND WHERE APPROVED BY VA.
2. COUPLINGS SHALL NOT BE USED ON HOT WATER SYSTEMS.